

Signature

JUVERNITHEITE CHITCHIT

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT **System Location** NORELL AVE. N Telephone Number State MN ZIP 55082 Property ID No./GEO Code Pumping Date 9 Contractor MPCA License No. 915 Telephone Number 651-459-016 Maintainer MEYER SEWER Report Liquid Capacity in Gallons What was done to the system? Tank 1: /500 Pumped Tank 2: Pumped Tank(s) Pumped Pumped Tank 4: Pumped Sludge and scum measured. Do tanks need to be pumped? Total Gallons Pumped: 1500 Yes No (If no provide measurements below) NOTE: This does not serve as a compliance inspection. **Visual Inspection** (note any problems with the system): *Tank Measurements-Use Only If Tank(s) Were NOT Pumped in. **X** Tank Width in. **X** Tank Depth in. = Tank Volume (cubic inches) Tank Length in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches) Tank Radius Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch in. **X** Gallons Per Inch = Sludge Volume Gallons Studge Level in. **X** Gallons Per Inch = Scum Volume Gallons Scum Level Gallons + Scum Volume = Total Sludge and Scum Volume Sludge Volume Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank *Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet Scum Layer baffle: or Tank Depth measured 2. Total sludge and scum volume is greater Effluent from invert of outlet than 25 percent of the tank's liquid pipe to bottom of tank capacity. Sludge Layer Reset Form

Date