

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006/ Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 641 Owinner Anell	Telephone Number
	MNZIP 55043 Property ID No./GEO Code
	ping Date 8/3/10
Contractor	
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016	
, What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?  Yes No (If no provide measurements below)	Total Gallons Pumped: (Care)
Visual Inspection (note any problems with the system	n): NOTE: This does not serve as a compliance inspection.
The state of the s	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X	( Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X	( 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch =	
Scum Level in. X Gallons Per Inch =	Scum Volume Gallons
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Ca	apacity = Percent Sludge and Scum in Tank %
Total Studge and Scuri Volume	
e F	*Tanks must be pumped if either of the following conditions exist:
	1. The top of the sludge layer is less than
Scum Layer	12 inches from the bottom of the outlet
Effluent	Tank Depth measured baffle; or 2. Total sludge and scum volume is greate
	than 25 percent of the tank's liquid
Sludge Layer	capacity.
	Reset Form
Signature	Date S/3//S Reset Form