

DEPARTMENT OF PUBLIC MEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

			S	ystem Lo	cation	·		
Address 13955 28th CFA				Telephone Number				
City Stillweter State				re MU ZIP 55082 Property ID No./GEO Code				
Owner Brigh	Bable	u An		nping Date (1/17/15				
				Contrac	tor			
Maintainer MEY	ER J	SEWER_	MPCA	License N	0. 91.	5	Telephone Number 65/-	459-016
What was done to the system?				Report Liquid Capacity in Gallons				
🔏 Tank(s) Pumped				Tank 1: /2009 Pumped Tank 2: Pumpe				· Pumpecy
Sludge and scum measured.					Tank 3:		Pumped Tank 4:	Pumped
Do tanks need to be pumped? Yes Do (If no provide measurements below)					Total Ga	lons Pump	ed: / <i>200</i>	-
Visual Inspection (ı) :	NOTE: This does not serve as a compliance inspection					
		*Tank Meas	urements-l	Jse Only I	If Tank(s)	Were NOT	Pumped	
Tank Length	in. X	Tank Width	in. X	Tank Der	pth	in. =	Tank Volume (cubic inches)	
Tank Radius	in. χ	Tank Radius	in. X	3.14 =	= Tank Vo	 olume (cubi	c inches)	
Tank Volume (cu. in.)		/ 231.01 =	Liquid Ca	pacity		Gallons / T	fank Depth in. = Gallor	is/Inch
Sludge Level	in. X	Gallons Per Inch	= 9	Sludge Vol	lume	Gallor	ns	
Scum Level	in. 🗶	Gallons Per Inch	== <u>C</u>	Scum Volu	ime	Gallon	os	
Sludge Volume	-	Scum Volume	= 1	otal Slude	ge and Scu	ım Volume	Gallons	
Total Sludge and Scu	ım Volu	me /	Liquid Cap	acity	=	Percent S	ludge and Scum in Tank	%
Scum Layer Effluent Sludge Layer				from	Depth me invert of c to bottom	outlet	*Tanks must be pumped if following conditions exist: 1. The top of the sludge lay 12 inches from the bottom baffle; or 2. Total sludge and scum ve than 25 percent of the tank capacity.	er is less than of the outlet olume is greate