

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 2811 Norcrest Ame N	Telephone Number
	V ZIP 5 5082 Property ID No./GEO Code
Owner Tom Horrsperger Pumping	Date 10/27/15
C	ontractor
Maintainer MEYER SEWER MPCALice	ense No. 915 Telephone Number 651-459-014
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /200 X Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: /2009
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
	JAN 07 2016
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Ta	ink Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3	.14 = Tank Volume (cubic inches)
Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Slud	lge Volume Gallons
Scum Level in. X Gallons Per Inch = Scur	m Volume Gallons
Sludge Volume + Scum Volume = Tota	Il Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacit	ty = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greated than 25 percent of the tank's liquid capacity.