

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

33 13 MAINTENANCE REPORT				
System Location				
Address 952/ S	+: Munter Bh	d N		Telephone Number
City Lake Elm	<b>6</b>	State MATZ	IPSSOULD Pro	perty ID No./GEO Code
Owner Rick H	asch	Pumping Date		
Contractor				
Maintainer MEYER	SEWER	MPCA License N	0. 915	Telephone Number 651-459-016
What was do	ne to the system?		Repo	ort Liquid Capacity in Gallons
Tank(s) Pumped Sludge and scum meas Do tanks need to be pu	elow)		Pumped Tank 2: Pumped  Pumped Tank 4: Pumped  ped: 2500	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection				
	*Toole #		4T-1/2) W 400	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped				
Tank Length in.	X Tank Width	in. <b>X</b> Tank De	oth in. =	Tank Volume (cubic inches)
Tank Radius in.	χ Tank Radius	in. <b>X 3.14</b> =	: Tank Volume (cut	oic inches)
Tank Volume (cu. in.)	/ 231.01 = Lic	quid Capacity	Gallons /	Tank Depth in. = Gallons/Inch
Słudge Level in.	X Gallons Per Inch	= Sludge Vo	ume Gallo	ns
Scum Level in.	X Gallons Per Inch	= Scum Volu	me Gallo	ns
Sludge Volume	+ Scum Volume	= Total Slude	ge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %				
Scum Layer  Effluent  Sludge Layer		from	Depth measured invert of outlet to bottom of tank	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.