

DEPARTMENT OF PUBLIC MEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		Syster	n Location	
Address 8266	Manning	AUE. S		Telephone Number
City Hastine		State M 1) ZIPSSO.33 Pro	perty ID No./GEO Code
Owner Janua	1 Wilbur	Pumping D	2	, no
		Con	ntractor	
Maintainer MEY	ER SEWER	MPCA Licen	ise No. 915	Telephone Number 651-459-016
What w	as done to the system?		Repo	ort Liquid Capacity in Gallons
Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements below)			· · · · · · · · · · · · · · · · · · ·	Pumped Tank 2: 1000 Pumper Pumped Tank 4: Pumper ped: 1000
Visual Inspection	(note any problems wi	th the system):	NOTE: This doe	es not serve as a compliance inspection
	*Tank Me	asurements-Use O	nly If Tank(s) Were NOT	Pumped
Tank Length	in. X Tank Width	in. X Tank	Oepth in. =	Tank Volume (cubic inches)
Tank Radius	in. X Tank Radius	in. X 3.1	4 = Tank Volume (cub	oic inches)
Tank Volume (cu. in	.) / 231.0 1	= Liquid Capacity	Gallons /	Tank Depthin. = Gallons/Inch
Sludge Level	in. X Gallons Per Inc	h = Sludge	e Volume Gallo	ns
Scum Level	in. X Gallons Per Inc	h = Scum	Volume Gallo	ns
Sludge Volume	+ Scum Volume	= Total S	Sludge and Scum Volume	Gallons
Total Sludge and Sc	:um Volume	/ Liquid Capacity	= Percent S	Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer			Fank Depth measured rom invert of outlet oipe to bottom of tank	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.
	114/		12/7/15	