

Signaturo

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System Lo	ocation		
Address 1296/	53rd S+N			Telephone Number	
City St. Wweter		State MM Z	CIPS SOBA Pro	perty ID No./GEO Code	
Owner Hary	Ma Napiwock	Pumping Date	10/21/15		
		Contra	ctor		
Maintainer MEYE	R SEWER	MPCA License N	10. 915	Telephone Number 651-459-016.	
What was done to the system?			Report Liquid Capacity in Gallons		
Tank(s) Pumped			Tank 1: 1500	Pumped Tank 2: Lead Pumped	
Sludge and scum measured.			Tank 3:	Pumped Tank 4: Pumped	
Do tanks need to be pumped? Yes No (If no provide measurements below)			Total Gallons Pumped: 2500		
	note any problems with th		NOTE: This do	es not serve as a compliance inspection.	
Visual hispection (i	note any problems with the	ic system).	1012. 1113 00	es not serve as a comprision aspection.	
	*Tank Measur	ements-Use Only	If Tank(s) Were NO	f Pumped	
Tank Length	in. X Tank Width	in. X Tank De	epth in. =	Tank Volume (cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3.14 :	= Tank Volume (cul	oic inches)	
Tank Volume (cu. in.)	/ 231.01 =	 Liquid Capacity	Gallons /	Tank Depth in. = Gallons/Inch	
Sludge Level	in. X Gallons Per Inch	= Sludge Vo	olume Gallo	ens ————————————————————————————————————	
Scum Level	in. X Gallons Per Inch	= Scum Vol	ume Gallo	ons	
				Callana	
Sludge Volume 	+ Scum Volume	= Total Sluc	lge and Scum Volum	e Gallons	
Total Sludge and Scu	ım Volume / L	iquid Capacity	= Percent	Sludge and Scum in Tank %	
				*Tanks must be pumped if either of the	
				following conditions exist:	
Scum Layer	1			1. The top of the sludge layer is less than 12 inches from the bottom of the outlet	
Effluent	- 19-	Tani	k Depth measured	baffle; or	
Emuem		fron	n invert of outlet	Total sludge and scum volume is greater than 25 percent of the tank's liquid	
Sludge Layer		pipe	pipe to bottom of tank capacity.		

Reset Form