

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location					
Address 4/48	Tours Chale M			Telephone Number	
City Lake El	no	State MUZI	PS 5042, Proj	perty ID No./GEO Code	
Owner Paul B	oker	Pumping Date	10/21/15		
Contractor					
Maintainer MEYE	RSEWER	MPCA License No	915	Telephone Number 651-43	59-016.
What wa		Report Liquid Capacity in Gallons			
Tank(s) Pumped		Tank 1: 1500 Pumped Tank 2: Pumped			
Sludge and scum in Do tanks need to l		Tank 3: Pumped Tank 4: Pumped			
Yes No	elow)	Total Gallons Pump	ped: 1500		
Visual inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.					inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped					
Tank Length	in. X Tank Width	in. X Tank Dep	oth in. =	Tank Volume (cubic inches)	
Tank Radius	in X Tank Radius	in. X 3.14 =	: Tank Volume (cub	oic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch					
Sludge Level	in. X Gallons Per Inch	= Sludge Vol	ume Gallo	ns	
Scum Level	in. X Gallons Per Inch	= Scum Volu	me Gallo	ns	
Sludge Volume	+ Scum Volume	= Total Sludg	ge and Scum Volume	Gallons	
Total Sludge and Scu	m Volume / Lie	quid Capacity	= Percent	Sludge and Scum in Tank	%
Scum Layer Effluent Sludge Layer		from	Depth measured invert of outlet to bottom of tank	*Tanks must be pumped if eit following conditions exist: 1. The top of the sludge layer 12 inches from the bottom of baffle; or 2. Total sludge and scum voluthan 25 percent of the tank's capacity.	is less than the outlet ime is greatei