

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location	
Address Gbl. Pawme Ave N	Telephone Number
City St. //water State M	V ZIPSSOR 2 Property ID No./GEO Code
Owner Sue Rosenbaum Pumping [
Co	ntractor
Maintainer MEYER SEWER MPCALice	nse No. 915 Telephone Number 651-459-011
What was done to the system?	Report Liquid Capacity in Gallons
	Tank 1: Pumped Tank 2: Pumpec
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: /200
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank	in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total	Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity	Percent Sludge and Scum in Tank
	*Ťanks must be pumped if either of the
	following conditions exist: 1. The top of the sludge layer is less than
Scum Layer II	12 inches from the bottom of the outlet
	Tank Depth measured baffle; or 2. Total sludge and scum volume is greate
	than 25 percent of the tank's liquid
Sludge Layer	capacity.