

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 1305 Quant Aus	Telephone Number
City Lakeland 5	tate UN ZIPS 3045 Property ID No./GEO Code
Owner Tim Zilles P	umping Date 12/3/5
	Contractor
Maintainer MEYER SEWER M	PCA License No. 915 Telephone Number 651-459-0162
What was done to the system?	Report Liquid Capacity in Gallons
X Tank(s) Pumped	Tank 1: 1000 Pumped Tank 2: 1000 Pumper
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below	
Visual Inspection (note any problems with the sys	
Visual inspection (note only problems with the sys	tem): NOTE: This does not serve as a compliance inspection
*Tank Measuremer	nts-Use Only If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width in.	χ Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in.	X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid	d Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid	Capacity = Percent Sludge and Scum in Tank 95
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.