

## DELAKIWENI OF LARPIC HEATIH AND FUNIKONWENI

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location						
Address <b>8050</b>	Quedrant Ave.	S		Telephone Number		
City Has Lh	as	State Mal ZIP	55033 Prop	perty ID No./GEO Code		
Owner Steve Amberson Pumping Date 10/20/15						
Contractor						
Maintainer MEY	ER SEWER	MPCA License No.	915	Telephone Number 651-4	159-016.	
What was done to the system?			Report Liquid Capacity in Gallons			
Tank(s) Pumped			Tank 1: Pumped Tank 2: Pumped			
Sludge and scum measured.			Tank 3: Pumped Tank 4: Pumped			
Do tanks need to be pumped?  Yes No (If no provide measurements below)			Total Gallons Pumped: 2000			
Visual Inspection	(note any problems with the	system):	NOTE: This does not serve as a compliance inspection.			
and the second s						
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped						
Tank Length	in. <b>X</b> Tank Width	in. <b>X</b> Tank Dept	h in. =	Tank Volume (cubic inches)		
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)						
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch						
Sludge Level in. <b>X</b> Gallons Per Inch = Sludge Volume Gallons						
Scum Level	in. <b>X</b> Gallons Per Inch	— = Scum Volum	ne Gallo	ns		
Sludge Volume	+ Scum Volume	— Total Sludge	and Scum Volume	. Gallons		
	<del> </del>			*	0/	
Total Sludge and Sc	rum Volume / Liq	uid Capacity	= Percent	Sludge and Scum in Tank	% 	
		<del>Fi</del>		*Tanks must be pumped if e	ither of the	
		<u> </u>		following conditions exist:  1. The top of the sludge layer	er is less than	
Scum Layer		<del>\                                    </del>		12 inches from the bottom	of the outlet	
Effluent			Depth measured nvert of outlet	baffle; or 2. Total sludge and scum vo	lume is greater	
Glidada		<b>S</b> 11	bottom of tank	than 25 percent of the tank's liquid capacity.		
Sludge Layer				ταρατιή.		