

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location	
Address 1667 Olone Auch	Telephone Number
City (2) 1/1/	te M / ZIP SCOSIZ Property ID No./GEO Code
Owner JOP Myetzinski Pur	pping Date 11/2/15
Contractor	
Maintainer MEYER SEWER MPC	A License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
 ✓ Tank(s) Pumped ☐ Sludge and scum measured. Do tanks need to be pumped? ☐ Yes ☐ No (If no provide measurements below) Visual Inspection (note any problems with the system 	Tank 1: Loco Pumped Tank 2: Loco Pumped Tank 3: Pumped Tank 4: Pumped Total Gallons Pumped: Doco NOTE: This does not serve as a compliance inspection
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in.)	(Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in.)	(3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch =	Sludge Volume Gallons
Scum Level in. X Gallons Per Inch =	Scum Volume Gallons
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Ca	apacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.