

520 Lafayette Road North St. Paul, MN 55155-4194

Compliance Inspection Form

Existing Subsurface Sewage Treatment Systems (SSTS)

Doc Type: Compliance and Enforcement

Inspection results based on Minnesota Pollution Control Agency (MPCA) requirements and attached forms – additional local requirements may also apply.	For local tracking purposes:
Submit completed form to Local Unit of Government (LUG) and system owner within 15 days	
System Status	
System status on date (mm/dd/yyyy):4/16/2020	
	pliant – Notice of Noncompliance e Requirements on page 3.)
Reason(s) for noncompliance (check all applicable) Impact on Public Health (Compliance Component #1) – Imminent threat to Other Compliance Conditions (Compliance Component #3) – Imminent the Tank Integrity (Compliance Component #2) – Failing to protect groundwa Other Compliance Conditions (Compliance Component #3) – Failing to protect groundwa Soil Separation (Compliance Component #4) – Failing to protect groundwa Operating permit/monitoring plan requirements (Compliance Component	reat to public health and safety ter rotect groundwater rater
Property Information Parcel ID# or Sec/Twp/Rar	28 021 21 42 0004
	for inspection: Point of sales
	phone: 651-982-1368 Debbie
or	priorie. <u>031-902-1300 Debbie</u>
Owner's representative: Represe	ntative phone:
Local regulatory authority: Washington County Regulatory	ory authority phone: 651-430-6679
Brief system description: 6000 gallon septic tank, 6000 galloon split tank, 2000 gal	lon pump tank with trenches
Comments or recommendations:	
No operating permit for this system	RECEIVED
	APR 2 9 2020
Certification	UBLIC HEALTH
I hereby certify that all the necessary information has been gathered to determine the determination of future system performance has been nor can be made due to unknown possible abuse of the system, inadequate maintenance, or future water usage.	compliance status of this system. No
	tion number: 7638
Business name: AT Septic Inspection & Design inc. Lice	nse number: 3886
Inspector signature: Any therpsen Ph	one number: 320-980-0235
Necessary or Locally Required Attachments	
☐ Soil boring logs ☐ System/As-built drawing ☐ Forms pe	r local ordinance

Compliance criteria:		Verification method(s):
System discharges sewage to the ground surface.	☐ Yes ☒ No	☑ Searched for surface outlet☑ Searched for seeping in yard/backup in home
System discharges sewage to drain tile or surface waters.	☐ Yes ☒ No	☐ Excessive ponding in soil system/D-boxes☐ Homeowner testimony (See Comments/Explanation)
System causes sewage backup into dwelling or establishment.	☐ Yes No	☐ "Black soil" above soil dispersal system ☐ System requires "emergency" pumping
Any "yes" answer above ind system is an imminent threa health and safety.		☐ Performed dye test ☐ Unable to verify (See Comments/Explanation) ☐ Other methods not listed (See Comments/Explanation)
Comments/Explanation:		
Tank Integrity — Compliance	component #2 of 5	
Compliance criteria:		Verification method(s):
System consists of a seepage pit, cesspool, drywell, or leaching pit.	☐ Yes ☒ No	☐ Probed tank(s) bottom☐ Examined construction records
Seepage pits meeting 7080.2550 may be compliant if allowed in local ordinance		☐ Examined Tank Integrity Form (Attach)
compliant if allowed in local ordinance. Sewage tank(s) leak below their	☐ Yes ☒ No	 ☐ Examined Tank Integrity Form (Attach) ☐ Observed liquid level below operating depth ☑ Examined empty (pumped) tanks(s)
compliant if allowed in local ordinance.		☐ Observed liquid level below operating depth☑ Examined empty (pumped) tanks(s)☐ Probed outside tank(s) for "black soil"
compliant if allowed in local ordinance. Sewage tank(s) leak below their designed operating depth.	☐ Yes ☒ No	 ☐ Observed liquid level below operating depth ☑ Examined empty (pumped) tanks(s) ☐ Probed outside tank(s) for "black soil" ☐ Unable to verify (See Comments/Explanation)
compliant if allowed in local ordinance. Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above income.	☐ Yes ☒ No	 ☐ Observed liquid level below operating depth ☑ Examined empty (pumped) tanks(s) ☐ Probed outside tank(s) for "black soil" ☐ Unable to verify (See Comments/Explanation)
compliant if allowed in local ordinance. Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incompleted to protect to the sewage tank to the system is failing to protect to the sewage tank.	☐ Yes ☒ No	 ☐ Observed liquid level below operating depth ☑ Examined empty (pumped) tanks(s) ☐ Probed outside tank(s) for "black soil" ☐ Unable to verify (See Comments/Explanation)
compliant if allowed in local ordinance. Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incompleted to protect to the sewage tank to the system is failing to protect to the sewage tank.	☐ Yes ☒ No	☐ Observed liquid level below operating depth☑ Examined empty (pumped) tanks(s)☐ Probed outside tank(s) for "black soil"
compliant if allowed in local ordinance. Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incompleted to protect to the sewage tank to protect to the sewage tank.	☐ Yes ☒ No	 ☐ Observed liquid level below operating depth ☑ Examined empty (pumped) tanks(s) ☐ Probed outside tank(s) for "black soil" ☐ Unable to verify (See Comments/Explanation)
compliant if allowed in local ordinance. Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incompleted in the system is failing to protect to Comments/Explanation:	☐ Yes ☒ No dicates the groundwater.	 □ Observed liquid level below operating depth □ Examined empty (pumped) tanks(s) □ Probed outside tank(s) for "black soil" □ Unable to verify (See Comments/Explanation) □ Other methods not listed (See Comments/Explanation)
Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incomplete to protect of the complete to the complete t	☐ Yes ☑ No dicates the groundwater.	□ Observed liquid level below operating depth □ Examined empty (pumped) tanks(s) □ Probed outside tank(s) for "black soil" □ Unable to verify (See Comments/Explanation) □ Other methods not listed (See Comments/Explanation)
Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incompliance comments (Explanation: Other Compliance Condition a. Maintenance hole covers are dant b. Other issues (electrical hazards, etc.)	Tyes ⊠ No dicates the groundwater. Pins – Compliance compaged, cracked, unsecured.	□ Observed liquid level below operating depth □ Examined empty (pumped) tanks(s) □ Probed outside tank(s) for "black soil" □ Unable to verify (See Comments/Explanation) □ Other methods not listed (See Comments/Explanation) ponent #3 of 5 ed, or appear to be structurally unsound. □ Yes* ☑ No □ Unkersely impact public health or safety. □ Yes* ☑ No □ Unkersely impact public health or safety. □ Yes* ☑ No □ Unkersely impact public health or safety. □ Yes* ☑ No □ Unkersely impact public health or safety. □ Yes* ☑ No □ Unkersely impact public health or safety. □ Yes* ☑ No □ Unkersely impact public health or safety. □ Yes* ☑ No □ Unkersely impact public health or safety. □ Yes* ☑ No □ Unkersely impact public health or safety.
Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incompliance comments/Explanation: Other Compliance Conditional Maintenance hole covers are danged.	Tyes ⊠ No dicates the groundwater. Pins – Compliance compaged, cracked, unsecured.	□ Observed liquid level below operating depth □ Examined empty (pumped) tanks(s) □ Probed outside tank(s) for "black soil" □ Unable to verify (See Comments/Explanation) □ Other methods not listed (See Comments/Explanation) ponent #3 of 5 ed, or appear to be structurally unsound. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety.
Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incompliance comments (system is failing to protect (system is an imminent threat system is an imminent threat	Tyes ⊠ No dicates the groundwater. Pins – Compliance compaged, cracked, unsecured.	□ Observed liquid level below operating depth □ Examined empty (pumped) tanks(s) □ Probed outside tank(s) for "black soil" □ Unable to verify (See Comments/Explanation) □ Other methods not listed (See Comments/Explanation) ponent #3 of 5 ed, or appear to be structurally unsound. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety. □ Yes* ☑ No □ Unknersely impact public health or safety.
Sewage tank(s) leak below their designed operating depth. If yes, which sewage tank(s) leaks: Any "yes" answer above incompliance comments/Explanation: Other Compliance Condition a. Maintenance hole covers are dank b. Other issues (electrical hazards, etc *System is an imminent threat	Tyes No dicates the groundwater. Pins – Compliance compaged, cracked, unsecured to immediately and advito public health and safetal did water for other conditions.	□ Observed liquid level below operating depth □ Examined empty (pumped) tanks(s) □ Probed outside tank(s) for "black soil" □ Unable to verify (See Comments/Explanation) □ Other methods not listed (See Comments/Explanation) □ Other methods not listed (See Comments/Explanation) ed, or appear to be structurally unsound. □ Yes* ☑ No □ Unkneersely impact public health or safety. □ Yes* ☑ No □ Unkneety.

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31b • 6/4/14 Page 2 of 3

roperty address:		Inspector initials/Date:	AT 4/16/2020 (mm/dd/yyyy)
1. Soil Separation — Compliance co	omponent #4 of 5		(ттистуууу)
Date of installation: 10/30/1997	Unknown	Verification method(s):	
(mm/dd/yyyy) Shoreland/Wellhead protection/Food beverage odging?	☐ Yes No	Soil observation does not expire. Pro observations by two independent pa unless site conditions have been alto	nties are sufficient,
Compliance criteria:		requirements differ.	
For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead	☐ Yes ☐ No	☑ Conducted soil observation(s) (A	
Protection Area or not serving a food,		☐ Two previous verifications (Attact	10000 4000 00
everage or lodging establishment:		Not applicable (Holding tank(s), no	drainfield)
Prainfield has at least a two-foot vertical		☐ Unable to verify (See Comments/E	xplanation)
eparation distance from periodically aturated soil or bedrock.		☐ Other (See Comments/Explanation)	
lon-performance systems built April 1,	⊠ Yes □ No	Comments/Explanation:	
1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, peverage, or lodging establishment:		See attached map for installation	
Orainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*			
Experimental", "Other", or "Performance"	☐ Yes ☐ No	Indicate depths or elevations	
ystems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 1350 or 7080.2400 (Advanced Inspector		A. Bottom of distribution media	12-30"
icense required)		B. Periodically saturated soil/bedrock	54-66"
rainfield meets the designed vertical eparation distance from periodically attracted soil or bedrock.		C. System separation	36"
		D. Required compliance separation*	36"
Any "no" answer above indicates to ailing to protect groundwater. Operating Permit and Nitroger		*May be reduced up to 15 percent if Ordinance.	Not applicable
operating remine and microger	TOME - Complian	ice component #3 or 3	vot applicable
Is the system energial under an Operation	Pormit?	□ No. If "vee" A below is requir	un d
Is the system operated under an Operating		□ No If "yes", A below is requi	
Is the system required to employ a Nitroge	n BMP? ☐ Yes	☐ No If "yes", B below is require	
	n BMP? ☐ Yes	☐ No If "yes", B below is require	
Is the system required to employ a Nitroge	n BMP? Yes	☐ No If "yes", B below is required	
Is the system required to employ a Nitroge BMP = Best Management Practice(s) If the answer to both questions is "I	n BMP? Yes	☐ No If "yes", B below is required	
Is the system required to employ a Nitroge BMP = Best Management Practice(s) If the answer to both questions is "I Compliance criteria	n BMP? Yes	□ No If "yes", B below is required design es not need to be completed.	
Is the system required to employ a Nitroge BMP = Best Management Practice(s) If the answer to both questions is "I Compliance criteria a. Operating Permit number:	n BMP? ☐ Yes specified in the system no", this section doe	☐ No If "yes", B below is required	
Is the system required to employ a Nitroge BMP = Best Management Practice(s) If the answer to both questions is "I Compliance criteria	n BMP? Yes specified in the system no", this section does ents been met?	□ No If "yes", B below is required design es not need to be completed. □ Yes □ No	

Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.

Please he as complete as 1955	ile, include all of the ligns listed below where applic	Tax Parcel)
GENERAL CHECKUST []-scalo []-north arrow []-lot dimensions []-structure location []-side lot aetback []-road aetback []-road aetback []-fendinfield location []-diainfield location []-location of all wells within 100' of drainfield []-fill & grading limits []-vegatation alteration limits	WATER RESOURCE CHECKLIST []-location of Roodway []-location of Roodway []-location of Roodway high water level (OHWL) []-location of present water line []-setback from OHWL []-location of highest known water-level []-existing local drainage []-location of wetland areas	Drawing By: Date of Drawing: Date of Drawing: System has Alternation Pawes
The second secon	132nd Street	4 4
Hadrey Circle IV	240'± Drawage way O mor	renews 70-100 are 70-100 social or the constant of the constant or the const

SEWAGE TREATMENT PROGRAM ONSITE

Client:

Vegetation:

Depth (in)

0-10"

10-30"

30-54"

54-60"

Soil Observation Log

Project ID:

v 04.01.2020

Consistence Loose Loose Loose Loose Elevation-relative to benchmark: Limiting Layer Elevation: 04/16/20 Organic Matter Auger 28.031.21.43.0004 -- Structure---Grade Weak Weak Weak Weak ☐ Bedrock Date Observation Type: Granular Granular Granular Granular Shape Linear, Linear Alluvium Location / Address: Indicator(s) S 10:00 AM Slope shape Redox Kind(s) Depletions □ Loess East of Sytem Soil survey map units: Mottle Color(s) 7.5YR 5/8 7.5YR 6/2 Back/Side Slope Slope %: Sunny Matrix Color(s) White Oak Heights 10YR 4/6 10YR 5/3 10YR 3/3 10YR 5/3 Soil parent material(s): (Check all that apply) Frag. % 35-50% 35-50% 35-50% <35% Rock Weather Conditions/Time of Day: Landscape Position: (select one) Grass Coarse Sand Coarse Sand Observation #/Location: Coarse Sand **Texture** Sand

(License #) 3886 hereby certify that I have completed this work in accordance with all applicable ordinances, rules and laws. Comments Mottling at 54" Mottling Colors are 7.5YR 5/8 & 6/2. Soils are wet after 54" (Signature) (Designer/Inspector) Amy Thompson

4/16/2020

(Date)

ONSITE SEWAGE TREATMENT PROGRAM

Soil Observation Log

Project ID:

v 04.01.2020

Client:		Wh	White oak heights	ights		Locati	Location / Address:		28.031.21.43.0004	3.0004
Soil parent n	Soil parent material(s): (Check all that apply)	eck all th	lat apply)	5	✓ Outwash	ne 🗌 Loess 🗍 Till	Till Alluvium	ium 🗌 Bedrock		Organic Matter
Landscape P	Landscape Position: (select one)	t one)	Back/Side Slope		Slope %:	Slope shape	Linear	Linear, Linear	Elevatio	Elevation-relative to benchmark:
Vegetation:		Grass		Soil !	Soil survey map units:				Limiting Layer Elevation:	r Elevation:
Weather Cor	Weather Conditions/Time of Day:	of Day:		Sunny	ny	10:00 AM	AM	Date		04/16/20
Observation	Observation #/Location:	7			west of system	em	esq0	Observation Type:		Auger
Depth (in)	Texture	Rock	Matrix Color(s)	lor(s)	Mottle Color(s)	Redox Kind(s)	Indicator(s)	1	Structure-	
•		Frag. %		,	,			Shape	Grade	Consistence
0	Sand	<35%	10YR 3/3	/3				Granular	Weak	Loose
7 23"		25 50%	10YR 4/4	/4				refinder	Jeom	6300
C7-1	Coalse salid	%0C-CC						Olaliutai	Near	25007
73-43"	haes esseed	35,50%	10YR 4/6	9/				Granular	Weak	9300
C+-C7	coalse saild	%00-cc						O a lata	nean	3000
	baes esseo	35-50%	10YR 5/3	(3				Granular	Weak	9,00
00-0	Coal se salid	%00-00						O di	No.	
87 77	Part) (12800))E E00/	10YR 5/3	/3	7.5YR 5/8	Depletions	51	Granular	JeoM	9300
99-99	Coarse sailu	%0C-CC			7.5YR 6/2			Granutai	Weak	Propaga
				4.53						
Comments	Comments Mottling at 66" Mottling colors are 7.5YR 5/8 & 6/2	" Mottling	colors are	7.5YR 5	/8 & 6/2					
I hereby cert	ify that I have c	completed	this work it	accord	lance with all appl.	hereby certify that I have completed this work in accordance with all applicable ordinances, rules and laws.	rules and law			
Ā	Amy Thompson		3	200	- Property	- A		3886		4/16/2020
(nes	(Designer/Inspector)	r)	,	1	(Signature)	(6)		(License #)		(Date)

AT SEPTIC INSPECTIONS & DESIGN INC. 49861 GOVERNMENT RD RUSH CITY MN 55069 320-980-0235

Date: 4/16/2020

Address:

PID #: 28.031.21.43.0004



6000 gallon septic tank



Inlet of 1st 6000 gallon tank



Inside the 1st 6000 gallon tank



Outlet of the 1st 6000 gallon tank



Floor of the 6000 gallon tank



Floor of the 1st 6000 gallon tank




2nd 6000 gallon split tank



Inlet of 1st chamber of 2nd 6000 gallon

tank



Floor of the 1st chamber of the 2nd 6000

gallon tank



6000 gallon tank

Side Wall of the 1st chamber of the 2nd



2nd 6000 gallon tank

Side wall and end wall of 1st chamber of



Center wall of the 2nd 6000 gallon tank



 2^{nd} chamber of the $2^{nd}\ 6000$ gallon tank



Inlet of the 2nd chamber of the 2nd 6000

gallon tank



Side wall of the second chamber of the 2nd

6000 gallon tank



Side wall of the 2nd chamber of the 2nd

6000 gallon tank



gallon tank

Outlet of the 2nd chamber of the 2nd 6000




gallon tank

Floor of the 2nd chamber of the 2nd 6000



200o gallon pump tank



Inside the pump tank




Side wall




walls and supports



Side wall and pumps



Floor and pumps



System area



System area and soil boring 1



System area and soil boring 2



System area

AT Septic Inspections & Design Inc. Disclaimer Sheet Relative to Subsurface Sewage Treatment System Compliance Inspection

- This inspection/report is being performed for only the seller/owner of the property on which the septic system
 located; there is no contract between AT Septic Inspections & Design Inc. and any other party except seller/owner
 unless otherwise noted. In such case that the buyer of the property is paying for the inspection, the contract is
 between only the buyer of the property and AT Septic Inspections & Design Inc.; there is no contract with any other
 party unless otherwise noted.
- 2. AT Septic Inspections & Design Inc. has not been retained to warranty, guarantee, or certify the proper functioning of the system for any period of time beyond the date of inspection or into the future. Because of the numerous factors (usage, maintenance, soil characteristics, previous failures, etc.) which may affect the proper operation of a septic system, as well as the inability of AT Septic Inspections & Design Inc. to supervise or monitor the use or maintenance of the system, the report shall not be construed as a warranty by AT Septic Inspections & Design Inc. that the system will function properly for any particular party for any period of time.
- 3. Minimum Compliance Inspection requirements relative to this inspection and this report include only verification that the septic system has tank(s)(septic tanks, lift tanks, dosing tanks, stilling tanks, etc.) which are watertight below the designed operating depth, the required separation between the bottom of the subsurface soil distribution medium and seasonally saturated soils, no back-ups of sewage into the dwelling, no discharge of sewage/effluent to the ground surface or surface waters, and no imminent safety hazards. AT Septic Inspections & Design Inc. does not inspect basement ejector pumps or exterior lift tank pumps and associated components as these are considered to be maintenance items. Sewage back-up verification is limited to observing the floor drain area and/or the information supplied by the last occupants of the building prior to inspection. AT Septic Inspections & Design Inc. cannot guarantee that the information given to them by the last occupants of the building prior to inspection relative to back-up is accurate. Some persons may attempt to hide or conceal signs of previous back-ups.
- 4. Certification of this system does not warranty future use beyond the date of the inspection. Any system, old or new, can become hydraulically overloaded or discharge sewage/effluent to the ground surface as a result of more people moving into the house than were previously occupying the house, improper maintenance, heavy usage, leaking plumbing fixtures, groundwater infiltration, tree roots, freezing conditions, surface drainage problems, poor initial design, poor conditions practices, or unsuitable materials used in constructing the system; The system can also simply stop working because of its age. The average life expectancy of a system that has been properly designed, installed, properly maintained, and used in the manner for which the system was designed can be expected to provide service for twenty to twenty-five years. Some parts of the system such as alarms, switches, pumps, and filters will most likely have to be replaced over the lifetime of the system.
- 5. A compliance Inspection is not meant to be a test or inspection for longevity of the system; a compliance inspection is strictly for the purpose of determining if the system is protective of public health and safety and is protective to groundwater at the date and time the inspection was performed. This inspection is not intended to determine if the system was originally designed or installed to past or present MPCA or other Local Government Unit code requirements. This inspection is not intended t determine if the system was designed and/or installed to support the anticipated flow from the building as the use of the building may have changed since the design and construction of the system due to the addition of bedrooms, occupants, etc. In addition, this inspection is not intended to determine the quality of the original systems design, the quality of the construction practices used while installing the system, or the quality of the materials used in constructing the system.
- 6. Winter Work: Client (persons paying for inspection) understands that inspections conduced during winter weather (approximately November 1st through April 1st) are more difficult to perform because of possible snow cover and/or ground frost. System components such as tanks, maintenance covers, tank inspection pipes, subsurface distribution medium inspection pipes, and soil treatment area more difficult or impossible to locate due to snow cover and/or ground frost. In addition soil borings are more difficult to perform due to snow cover and/or ground frost. AT Septic Inspections & Design Inc. will attempt to use the same level of standards when performing work during winter periods as when performing work during non- winter periods. However, client understands that because of the aforementioned considerations, the same level of standards may not be possible.
- By accepting this report, the client understands that AT Septic Inspections & Design Inc. will not be responsible for any monetary damages exceeding the fee of the service provided.