

Signatura all

## GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location System Location	
Address 3294 Oakgreen AUE.	Telephone Number
City 5 to / Water State MN ZIPS 5087 Property ID No./GEO Code	
Owner Lanny Goldsmith Pumping Date 10/19/15	
Contractor	
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016	
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped  Sludge and scum measured.  Do tanks need to be pumped?  Yes No (If no provide measurements below)	Tank 1: 1500 Pumped Tank 2: 1000 Pumped  Tank 3: Pumped Tank 4: Pumped  Total Gallons Pumped: 2500
Visual inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped  Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)  Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. <b>X</b> Gallons Per Inch = Scum Vo	olume Gallons
Sludge Volume + Scum Volume = Total Slu	udge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
fro	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Reset Form