

Signature /

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 13854 1542 54.	Telephone Number
City Afton State MW ZIP 5500 / Property ID No./GEO Code	
Owner Jim Moris	Pumping Date 10/19/15
Contractor/	
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped >	Tank 1: 1000 Pumped Tank 2: 1000 Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?	Taral Callers Durmond
Yes No (If no provide measurements b	pelow)
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. <b>X</b> Tank Width	in. <b>X</b> Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. <b>X</b> Tank Radius	in. <b>X</b> 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = L	iquid Capacity Gallons / Tank Depth in. = Gallons / Inch
Sludge Level in. <b>X</b> Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. <b>X</b> Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
Scum Layer  Effluent  Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Date 10)

Reset Form