

DELAKIWENT OF HARFIC HEATTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 27/5 Lake Elm	Telephone Number
	StateMN ZIP55042 Property ID No./GEO Code
Owner Dennis Trem!	Pumping Date 10/19/15
Contractor	
Maintainer MEYER SEWER N	APCA License No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: / 2005 Pumped Tank 2: Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below	w) Total Gallons Pumped: 1200
Visual Inspection (note any problems with the sy	stem): NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width ir	
Tank Radius in. X Tank Radius in	n. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid	d Capacity = Percent Sludge and Scum in Tank %
	Manufacture of the control of the co
	*Tanks must be pumped if either of the following conditions exist:
Scum Layer	1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
	Tank Darah managed baffle; or
Effluent	from invert of outlet 2. Total studge and scum volume is greater than 25 percent of the tank's liquid
Sludge Layer	pipe to bottom of tank capacity.

Reset Form