

Cianatura

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 14747 7046545	Telephone Number
City Hasthas State	MM ZIP 55033 Property ID No./GEO Code
Owner Sifke Suprem Pumping Date 10/18/15	
Contractor	
Maintainer MEYER SEWER MPCAL	icense No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1500 X Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?	A
Yes No (If no provide measurements below)	Total Gallons Pumped: /500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
	910S & I NAL
	(22) Extern
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. <b>X</b> Tank Width in. <b>X</b>	Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. <b>X</b> Tank Radius in. <b>X</b>	3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. <b>X</b> Gallons Per Inch = Slu	udge Volume Gallons
Scum Level in. <b>X</b> Gallons Per Inch = Sc	um Volume Gallons
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank 96	
Scum Layer  Effluent  Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Data

Reset Form