

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

			Sy:	stem Locat	ion			
Address 3330)	Lampert	AUE	. N		Telephone Number		
City Lake	J	Elmo			55402 Pro	perty ID No./GEO Code /	13.029.21.3	
Owner Davic	Q	Leng 42/		ng Date /	1/9/15		007/	
				Contractor				
Maintainer MEY	ER_	SEWER	MPCA LI	icense No.	915	Telephone Number 6:	51-459-0162	
What was done to the system?				Report Liquid Capacity in Gallons				
Tank(s) Pumped				Ta	ank 1: 700	Pumped Tank 2: Pumper		
Sludge and scum measured.						Pumped Tank 4;	Pumped	
Do tanks need to be pumped? Yes Do (If no provide measurements below)				Total Gallons Pumped: 700				
Visual Inspection (£		es not serve as a comp	pliance inspection	
		ny dingananana aka 1 sa 4 sa ka kasanban kasansa nasa			-			
		*Tank Mea	surements-Us	ie Only If T	ank(s) Were NOT	Pumped		
Tank Length	in.	X Tank Width	in. X	Tank Depth	in. =	Tank Volume (cubic inc	hes)	
Tank Radius	in.	χ Tank Radius	in. X	3.14 =	Tank Volume (cub	oic inches)		
Tank Volume (cu. in.))	/ 231.01 :	= Liquid Capa	acity	Gallons /	Tank Depth in. = 0	Sallons/Inch	
Sludge Level	in.	X Gallons Per Inch	= \$10	udge Volun	ne Gallo	ns		
Scum Level	in.	X Gallons Per Inch	= 5c	um Volume	e Gallo	ns		
Sludge Volume		+ Scum Volume	= To	ital Sludge a	and Scum Volume	Gallons		
Total Sludge and Scu	ım Vo	lume	/ Liquid Capa	city	= Percent !	Sludge and Scum in Tank	%	
Scum Layer						*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet		
Effluent Sludge Layer	fluent			Tank Depth measured from invert of outlet pipe to bottom of tank		baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.		
Jidoge cayer				-				