

Cianatura

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

| System Location | |
|--|--|
| Address 7555 Lanely Am S | Telephone Number |
| City Coffage Greve State | MWZIP SSOIL6 Property ID No./GEO Code |
| Owner Anna Edurado Pumping Date 10/16/15 | |
| Contractor | |
| Maintainer MEYER SEWER MPCA | License No. 915 Telephone Number 651-459-016 |
| What was done to the system? | Report Liquid Capacity in Gallons |
| Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements below) | Tank 1: 1500 Pumped Tank 2: Pumped Tank 3: Pumped Tank 4: Pumped Total Gallons Pumped: 1500 |
| Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection. | |
| *Tank Measurements-Use Only If Tank(s) Were NOT Pumped | |
| Tank Length in. X Tank Width in. X | Tank Depth in. = Tank Volume (cubic inches) |
| Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches) | |
| Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch | |
| Sludge Level in. X Gallons Per Inch = | Sludge Volume Gailons |
| Scum Level in. X Gallons Per Inch = | Scum Volume Gallons |
| Sludge Volume + Scum Volume = | Total Sludge and Scum Volume Gallons |
| Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank % | |
| Scum Layer Effluent Sludge Layer | *Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity. |

Date

Reset Form