

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

| System Location  |  |
|--|--|
| Address 14355 1546 5+ 11   | Telephone Number   |
| City St. Muratan State   | MNZIP 55082 Property ID No./GEO Code   |
| Owner I'm Krapelnicki Pum  | ping Date 10/16/15   |
| Contractor   |  |
| Maintainer MEYER SEWER MPC   | A License No. 915 Telephone Number 651-459-016   |
| What was done to the system?   | Report Liquid Capacity in Gallons  |
| Tank(s) Pumped   | Tank 1: Pumped Tank 2: Pumped  |
| Sludge and scum measured.  | Tank 3: Pumped Tank 4: Pumped  |
| Do tanks need to be pumped?  Yes No (If no provide measurements below)                     | Total Gailons Pumped: 2 (2000)   |
| Visual Inspection (note any problems with the system                                       |  |
| THOTE. THIS does not serve as a compliance inspection.                                     |  |
|  |  |
|  |  |
|  |  |
|  |  |
| *Tank Measurements-Use Only If Tank(s) Were NOT Pumped                                     |  |
| Tank Length in. <b>X</b> Tank Width in. <b>X</b>   | Tank Depth in. = Tank Volume (cubic inches)  |
| Tank Radius in. <b>X</b> Tank Radius in. <b>X</b>  | 3.14 = Tank Volume (cubic inches)  |
| Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch |  |
| Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons                                |  |
|  |  |
| Scum Level in. <b>X</b> Gallons Per Inch =   | Scum Volume Gallons  |
| Sludge Volume + Scum Volume =  | Total Sludge and Scum Volume Gallons   |
| Total Sludge and Scum Volume / Liquid Ca   | pacity = Percent Sludge and Scum in Tank %   |
| Scum Layer Scum Layer  | *Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet             |
| Effluent   | Tank Depth measured from invert of outlet pipe to bottom of tank baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity. |
| Sludge Layer   |  |