

Cianatura

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 5777 Hishland CAN	Telephone Number
City 1	P55042 · Property ID No./GEO Code
Owner Just in Nelson Pumping Date 18/5/	
Contractor /	
Maintainer MEYER SEWER MPCA License No.	o. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /500 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: 1500
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
NOTE: 1113 does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volu	me Gallons
Sludge Volume + Scum Volume = Total Sludg	ge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
from	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Reset Form