

Signatura

## DESAKTMENT OF SARPIC HEALTH AND FUSIKONWENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

		System Lo	cation		
Address 10649	Otchlowe	Anel		Telephone Number	
City Stollwast		State /// ZI	P55083 Pr	operty ID No./GEO Code	
Owner J. (m. M.	heres	Pumping Date	10/15/15		
		Contrac	tor		
Maintainer MEY	RSEWER	MPCA License N	0. 915	Telephone Number 651-459-	016.
What wa	s done to the system?		Rep	ort Liquid Capacity in Gallons	
Tank(s) Pumped		Tank 1: Islan Pumped Tank 2: Pumped			
Sludge and scum  Do tanks need to		Tank 3: Pumped Tank 4: Pumped			
·	below)	Total Gallons Pumped: <u>(500</u>			
Visual Inspection (note any problems with the system			: NOTE: This does not serve as a compliance inspection.		
Tank Longth	<del>, , , , , , , , , , , , , , , , , , , </del>	rements-Use Only l			
Tank Length	in. <b>X</b> Tank Width	in. <b>X</b> Tank De	oth in. =	Tank Volume (cubic inches)	
Tank Radius	in. <b>X</b> Tank Radius	in. <b>X 3.14</b> =	Tank Volume (cu	bic inches)	
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacity	Gallons /	Tank Depthin. = Gallons/Inch	
Sludge Level	in. <b>X</b> Gallons Per Inch	= Słudge Vo	lume Gall	ons	
Scum Level in. <b>X</b> Gallons Per Inch = Scum Volume Gallons			ons		
Sludge Volume	+ Scum Volume	= Total Slude	ge and Scum Volun	ne Gallons	
Total Sludge and Scu	ım Volume /	iquid Capacity	= Percen	t Sludge and Scum in Tank	%
Scum Layer  Effluent  Sludge Layer		from	Depth measured invert of outlet to bottom of tank	*Tanks must be pumped if either of following conditions exist:  1. The top of the sludge layer is less 12 inches from the bottom of the cobaffle; or  2. Total sludge and scum volume is than 25 percent of the tank's liquid capacity.	s than outlet s greater

Data

Reset Form