

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 1545 Queens Aue S	Telephone Number
City St Croix Beach State May 2	CIP 55(0)43 Property ID No./GEO Code
Owner Roser Norther & Pumping Date	
Contra	ctor
Maintainer MEYER SEWER MPCA License	No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /Sou Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?  Yes No (If no provide measurements below)	Total Gallons Pumped: 1500
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only	
Tank Length in. <b>X</b> Tank Width in, <b>X</b> Tank De	
Tank Radius in. X Tank Radius in. X 3.14	= Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity	Gallons / Tank Depthin. = Gallons/Inch
Sludge Level in. <b>X</b> Gallons Per Inch = Sludge Vo	olume Gallons
Scum Level in. <b>X</b> Gallons Per Inch = Scum Vol	ume Gallons
Sludge Volume + Scum Volume = Total Slud	dge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity	= Percent Sludge and Scum in Tank %
fron	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.