

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		Şystem	Location	**************************************	,	
Address 9320 7157 57. N			Telephone Number			
city Still Water	2	State M/V	ZIP55082 F	Property ID No./GEO Code		
Owner ROGER	Stowe !!	Pumping Da	te 10/29/15	y		
		Cont	ractor			
Maintainer MEYER	SEWER	MPCA Licens	e No. 915	Telephone Number 65/	-459-016	
What was done to the system?			Report Liquid Capacity in Gallons			
Tank(s) Pumped /			Tank 1: 1250	Pumped Tank 2:	☐ Pumpe n	
Sludge and scum measured. Do tanks need to be pumped?			Tank 3:	Pumped Tank 4;	Pumped	
Yes No (If no provide measurements below)			Total Gallons Pumped: 1250			
Visual Inspection (note		··	NOTE: This o	does not serve as a complia	nce inspection	
				Plan Chan Very har		
				JAN 1 1 2016		
				PUBLIC HEALT		
And the second s	*Tank Measur	ements-Use On	ly If Tank(s) Were N	OT Pumped		
Tank Length in.	X Tank Width	in, X Tank l	Depth in.	= Tank Volume (cubic inches)	
Tank Radius in.	χ Tank Radius	in X 3.14	= Tank Volume (c	rubic inches)		
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacity	Gallons	/ Tank Depth in. = Gallo	ons/Inch	
Sludge Level in.	X Gallons Per Inch	= Słudge	Volume Ga	llons	,	
Scum Level in.	X Gallons Per Inch	= Scum Ve	olume Ga	llons		
Sludge Volume -	+ Scum Volume	= Total Slu	udge and Scum Volui	me Gallons		
Total Sludge and Scum Vol	ume / L	iquid Capacity	= Percer	at Sludge and Scum in Tank	%	
				*Tanks must be pumped following conditions exis 1. The top of the sludge k	t:	
Scum Layer				12 inches from the botto	•	
Effluent		fro	Tank Depth measured from invert of outlet pipe to bottom of tank baffle; or 2. Total sludge and scum volume is great than 25 percent of the tank's liquid			
Sludge Layer				capacity.	capacity.	