

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System	Location		
Address 8925	274h57.	N		Telephone Number	
City Lales	Elmo	StateMN	ZIP55042 Pro	perty ID No./GEO Code	
Owner CRaic	i Novale	Pumping Da	te 10/29/15		
		Cont	ractor	,	······
Maintainer MEY	ER SEWER	MPCA Licens	e No. 915	Telephone Number 651-459-6	2162
What wa	s done to the system?		Repo	ort Liquid Capacity in Gallons	
Tank(s) Pumped Z			Tank 1:2250	Pumped Tank 2: 1250 Pun	npeny
Sludge and scum measured.			Tank 3:	` 	nped
Do tanks need to be pumped? Yes No (If no provide measurements below)			<u> </u>	ped: 2500	
	-				
	note any problems with	tne system):	NOTE: This do	es not serve as a compliance inspec	:t10f
	RECEVED				
	JAN 1 1 2016				
	" .				
	SIICHAIT				·
		urements-Use On	ly If Tank(s) Were NO	「Pumped	
Tank Length	in. X Tank Width	in, X Tank	Depth in. =	Tank Volume (cubic inches)	
Tank Radius	in. 🗶 Tank Radius	in. X 3,14	= Tank Volume (cub	oic inches)	
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacity	Gallons /	Tank Depthin. = Gallons/Inch	
Sludge Level	in. X Gallons Per Inch	= Sludge	Volume Gallo	ons	
Scum Level	in. X Gallons Per Inch	= Scum V	olume Gallo	ns	
Słudge Volume	+ Scum Volume	= Total SI	udge and Scum Volum	e Gallons	
Total Sludge and Scu	ım Volume /	Liquid Capacity	= Percent	Sludge and Scum in Tank %	
				"Tanks must be pumped if either of t following conditions exist: 1. The top of the sludge layer is less t	
Scum Layer	1000			12 inches from the bottom of the ou	
Effluent		fre	onk Depth measured om invert of outlet	baffle; or 2. Total sludge and scum volume is go than 25 percent of the tank's liquid	_j reat _t
Sludge Layer		pi	pe to bottom of tank	capacity.	
NAT	100000			/	·