

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6/30

SSTS MAINTENANCE REPORT

		System Lo	cation		· · · · · · · · · · · · · · · · · · ·
Address 8508) leambro Lue 5			Telephone Number	
City Coffag	- Conore		1P 5 50/6 Pr	operty ID No./GEO Code	
Owner Joe	dinsen	Pumping Date	10/22/15		······································
		Contrac	tor		
Maintainer MEY	ER SEWER	MPCA License N	0. 915	Telephone Number 65/-	459-016
What was done to the system?			Report Liquid Capacity in Gallons		
Tank(s) Pumped			Tank 1: 1500	Pumped Tank 2:	Pumped
Sludge and scum measured.			Tank 3:	Pumped Tank 4:	Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)			Total Gallons Pun	nped: 1500	_
	(note any problems with the	NOTE: This d	pes not serve as a compliance	ce inspection	
			- 		
		;			
			•		
	*Tank Measure	ments-Use Only	If Tank(s) Were NC	OT Pumped	
Tank Length	in. X Tank Width	in. X Tank De	oth in. =	Tank Volume (cubic inches)	
Tank Radius	in. 🗶 Tank Radius	in. X 3.14 =	= Tank Volume (cu	ubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch					
Sludge Level	in. X Gallons Per Inch	= Sludge Vo	lume Gall	ons	
Scum Level	in. X Gallons Per Inch	= Scum Volu	me Gall	ons	
Sludge Volume	+ Scum Volume	= Total Slude	ge and Scum Volun	ne Gallons	
Total Sludge and Scu	um Volume / Lic	 quid Capacity	= Percen	t Sludge and Scum in Tank	%
				*Tanks must be pumped if	either of the
following cor 1. The top of			following conditions exist:		
			1. The top of the sludge layer is less than 12 inches from the bottom of the outlet		
Effluent	- -	Tank	Depth measured	baffle; or	
MITGEIA		from	invert of outlet	 Total sludge and scum volume is greate: than 25 percent of the tank's liquid capacity. 	
Sludge Layer		pipe	to bottom of tank		