

OUTERIMENT CHITCH

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location		
Address 9757 Janero CAA	, 1	elephone Number
City Man-tomedi	State 11.10 1P 55/15 Prope	rty ID No./GEO Code
Owner Bill Brown	Pumping Date 9/19/15	
	Contractor	
Maintainer MEYER SEWER	MPCA License No. 915	elephone Number 651-459-016
What was done to the system?	Report	Liquid Capacity in Gallons
X Tank(s) Pumped	Tank 1: 15000 K	Pumped Tank 2: Pumped
Sludge and scum measured.		Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurement	Total Gallons Pumpe	d: 1500e)
		not serve as a compliance inspection.
Visual Inspection (note any problems with t	the system): NOTE. This does	That serve as a compliance inspection
*Tank Meası	urements-Use Only If Tank(s) Were NOT I	Pumped
Tank Length in. X Tank Width		Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic	
Tank Volume (cu. in.) / 231.01 =	Liquid Capacity Gallons / T.	ank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallon	S
	= Scum Volume Gallon	S
		Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume	
Total Sludge and Scum Volume /	Liquid Capacity = Percent SI	ludge and Scum in Tank
R I		*Tanks must be pumped if either of the following conditions exist:
Scum Layer Scum Layer		1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
	Tank Depth measured	baffle; or
Effluent	from invert of outlet	Total sludge and scum volume is greate than 25 percent of the tank's liquid
Sludge Layer	pipe to bottom of tank	capacity.