

Signature

COVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location **Address** Telephone Number) Property ID No./GEO Code City Owner Pumping Date Contracto MPCA License No. 915 Telephone Number 651-459-0161 Maintainer MEYER SEWER Report Liquid Capacity in Gallons What was done to the system? Tank 1: 800 Pumped Tank 2: 600 Pumped Tank(s) Pumped Pumped Pumped Tank 4: Sludge and scum measured. Tank 3: Do tanks need to be pumped? Total Gallons Pumped: Yes No (If no provide measurements below) NOTE: This does not serve as a compliance inspection. **Visual Inspection** (note any problems with the system): *Tank Measurements-Use Only If Tank(s) Were NOT Pumped in. X Tank Depth in. = Tank Volume (cubic inches) in. X Tank Width Tank Length in. \mathbf{X} Tank Radius in. \mathbf{X} 3.14 = Tank Volume (cubic inches) Tank Radius Gallons / Tank Depth in. = Gallons/Inch Tank Volume (cu. in.) / 231.01 = Liquid Capacity in. **X** Gallons Per Inch = Sludge Volume Sludge Level Gallons = Scum Volume in. X Gallons Per Inch Scum Level Gallons = Total Sludge and Scum Volume + Scum Volume Sludge Volume / Liquid Capacity = Percent Sludge and Scum in Tank Total Sludge and Scum Volume *Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet Scum Layer baffle: or Tank Depth measured 2. Total sludge and scum volume is greater Effluent from invert of outlet than 25 percent of the tank's liquid pipe to bottom of tank capacity. Sludge Layer Reset Form Date