

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 10475- 1144 st 1)	Telephone Number
City SHI Water State	MN ZIP55082 Property ID No./GEO Code
	ng Date 9/24/15
Contractor	
Maintainer MEYER SEWER MPCA	License No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Frank(s) Pumped /	Tank 1: 1250 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?	Total Control
Yes No (If no provide measurements below)	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Radius in. X Tank Radius in. X	3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = S	ludge Volume Gallons
Scum Level in. X Gallons Per Inch = S	cum Volume Gallons
Sludge Volume + Scum Volume = T	otal Sludge and Scum Volume Gallons
Total Sludge and Scum Volume/ Liquid Cap	acity = Percent Sludge and Scum in Tank %
	*Tanks must be pumped if either of the
	following conditions exist: 1. The top of the sludge layer is less than
Scum Layer II	12 inches from the bottom of the outlet
Effluent	Tank Depth measured baffle; or 2. Total sludge and scum volume is greater
	than 25 percent of the tank's liquid
Sludge Layer	capacity.
A Commence of the commence of	
Signature /	Date 124/15 Reset Form
V-C	