

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 5367 Jamaca Aux	Telephone Number
	NW ZIP 55042 Property ID No./GEO Code
	g Date 1///6/15
•	Contractor
Maintainer MEYER SEWER MPCALI	cense No. 915 Telephone Number 651-459-011
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1500 Pumped Tank 2: Pumper
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 1500
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection
*Tank Measurements-Us	e Only If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width in. X T	ank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X	3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capa	city Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch = Slu	dge Volume Gallons
Scum Level in. X Gallons Per Inch = Scu	m Volume Gallons
Sludge Valume + Scum Volume = Tot	al Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capac	ity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.