

Signature MU

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

	System Loc	ation	
Address 8573 Hidden	Ray Trai	//	Telephone Number
City Laker Elmer	State MN ZI	P55042 Pro	perty ID No./GEO Code
Owner Ivan Skoog	Pumping Date	9/25/15	
Contractor			
Maintainer MEYER SEWER	MPCA License N	0. 915	Telephone Number 651-459-016.
What was done to the system?		Repo	ort Liquid Capacity in Gallons
Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped?  Yes No (If no provide measurem	ents below)	Tank 1: /OUD Tank 3:	Pumped Tank 2: 1000 Pumped Pumped Tank 4: Pumped ped: 2000
Visual Inspection (note any problems wit	h the system):	NOTE: This doe	es not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped			
Tank Length in. <b>X</b> Tank Width	in. <b>X</b> Tank Dep	oth in. =	Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. <b>X</b> 3.14 =	Tank Volume (cub	oic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch			
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons			
Scum Level in. <b>X</b> Gallons Per Inch	= Scum Volu	me Gallo	ns
Sludge Volume + Scum Volume	= Total Sludg	ge and Scum Volume	Gallons
Total Sludge and Scum Volume	/ Liquid Capacity	= Percent !	Sludge and Scum in Tank%
Scum Layer  Effluent  Sludge Layer	from	Depth measured invert of outlet to bottom of tank	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Reset Form