

DEPARTMENT OF PUBLIC MEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location	
Address 5070 Radio Druve	Telephone Number
	ZIP 55/29 Property ID No./GEO Code
Owner Jary Spellman Pumping Date 11/17/15	
Contractor	
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-457-016	
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1200 Pumped Tank 2: Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumpec
Yes 1 No (If no provide measurements below)	Total Gallons Pumped: /20 🔾
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Table	
Tank Length in. X Tank Width in. X Tank D	Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gailons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Slu	dge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
fro	Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.