

OUTLINIMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location		
Address 9/17 Manning AUE.	N	Telephone Number
	MW ZIPS5082 Prop	erty ID No./GEO Code
Owner Lyle Burtzlaff Pumping Date 9/29/15		
Contractor		
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016		
What was done to the system?	Repo	rt Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 500 &	Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3:	Pumped Tank 4: Pumped
Do tanks need to be pumped?	Total Gallons Pump	ed: 500
Yes No (If no provide measurements below)		
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.		
	.0	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped		
Tank Length in. X Tank Width in. X	Tank Depth in. =	Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X	3.14 = Tank Volume (cub	ic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Ca	apacity Gallons/	Tank Depthin. = Gallons/Inch
Sludge Level in. X Gallons Per Inch =	Sludge Volume Gallo	ns
Scum Level in. X Gallons Per Inch =	Scum Volume Gallo	ns
	T	s Gallons
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume	
Total Sludge and Scum Volume / Liquid Ca	pacity = Percent	Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.
Signature /	Date 9/29/13	Reset Form