

## OO VERTAMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location						
Address 14301	1 104h 54	N		•	Telephone Number	
City 547/10	vater.	State <b>)</b> Mi	Uzir550	Prope	erty ID No./GEO Code	
Owner Krith Rut Kowski Pumping Date 9/30/15						
Contractor						
Maintainer MEYE	RSEWER	MPCA Lice	ense No. 91	5	Telephone Number 65 /	-459-016
What was done to the system?			Report Liquid Capacity in Gallons			
Tank(s) Pumped 2			Tank 1: 1000 Pumped Tank 2: 1000 Pumped			
Sludge and scum measured.  Do tanks need to be pumped?			Tank 3: Pumped Tank 4: Pumped			
Yes No (If no provide measurements below)			Total Gallons Pumped: 2000			
Visual Inspection (	note any problems with	the system):	NOTI	E: This does	not serve as a complia	nce inspection.
	¥T-1-84	surements-Use	Only If Tank/s	Word NOT	Pumpad	
						· ·
Tank Length	in. <b>X</b> Tank Width -	in. <b>X</b> Ta	nk Depth ——	in. =	Tank Volume (cubic inches	
Tank Radius	in. 🗶 Tank Radius	in. <b>X 3</b>	.14 = Tank\	/olume (cubi	c inches)	
Tank Volume (cu. in.)	/ 231.01	<ul> <li>Liquid Capaci</li> </ul>	ity	Gallons / T	ank Depthin. = Gall	ons/Inch
Sludge Level	in. <b>X</b> Gallons Per Inch	= Slud	ge Volume	Gallon	s	
Scum Level	in. <b>X</b> Gallons Per Inch	= Scur	m Volume	Gallon	5	
Sludge Volume	− + Scum Volume	= Tota	 I Sludge and So	 rum Volume	Gallons	
<del></del>	·	· • • • • • • • • • • • • • • • • • • •	-			%
Total Sludge and Scu	ım Volume	/ Liquid Capaci	ty	= Percent Si	ludge and Scum in Tank —	
		FI			*Tanks must be pumped	
					following conditions exist.  1. The top of the sludge l	ayer is less than
Scum Layer	T				12 inches from the botto baffle; or	m of the outlet
Effluent			Tank Depth m		2. Total sludge and scum	volume is greate
Sludge Layer	-		pipe to botto		than 25 percent of the ta capacity.	ink's liquid
Jidage Layer						
N.				/ /		
Signature /	//		Date //	30/15	Rese	t Form