

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 322 Manning AUE 5 Telephone Number	
City (1) State N ZIP 55/29 Property ID No./GEO Code	
Owner Doug Lamb Pumping Date 8/4/15	
Contractor	
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459	7-016
What was done to the system? Report Liquid Capacity in Gallons	ng (C. G. Suis
Talk 1. 70002 1 Talk 2.	Pumped
Sludge and scum measured.  Do tanks need to be pumped?  Tank 3: Pumped Tank 4: Image: Tank 3: Tank 3: Tank 3: Tank 4:	Pumped
☐ Yes ☐ No (If no provide measurements below) Total Gallons Pumped: 1000	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance ins	pection.
	·
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	y
Tank Length in. <b>X</b> Tank Width in. <b>X</b> Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	<u></u>
Sludge Level in. <b>X</b> Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. <b>X</b> Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank	% -
Scum Layer  Effluent  Tank Depth measured from invert of outlet pipe to bottom of tank  *Tanks must be pumped if either following conditions exist:  1. The top of the sludge layer is le 12 inches from the bottom of the baffle; or  2. Total sludge and scum volume than 25 percent of the tank's liquicapacity.	ess than outlet is greater