

Signature

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 9704 PROUDORNEE Road	7 Telephone Number
	ZIPS5/29 Property ID No./GEO Code
Owner Knistophen Draks Pumping Date 8/10/15	
Contractór	
Maintainer MEYER SEWER MPCA License	No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /500 Pumped Tank 2: Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: /500
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
,	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank I	Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14	= Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge N	/olume Gallons
Scum Level in. X Gallons Per Inch = Scum Vo	olume Gallons
Sludge Volume + Scum Volume = Total Slu	adge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
fro	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Reset Form