

OUTENMENT CHITCH

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

	System Location					
Address 8470	Lofton AUE	· N	Т	elephone Number		
City 5 15 1/1/1/1	later Sta	te MW Z	P55082 Prope	rty ID No./GEO Code		
Owner Casthaus Bavarian Huntin Pumping Date 9/11/15						
Contractór /						
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016						
What was	s done to the system?]	Report Liquid Capacity in Gallons			
Pank(s) Pumped	/		Tank 1: (200)	Pumped Tank 2:	Pumped	
Sludge and scum r	neasured.		Tank 3:	Pumped Tank 4:	Pumped	
Do tanks need to b	•		Total Gallons Pumped: 1200			
Tes 1 No (in no provide measurements below)					ce inspection.	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.						
		-				
	*Tank Measurement	s-Use Only	If Tank(s) Were NOT F	Pumped		
Tank Length		X Tank De		Tank Volume (cubic inches)		
	in. X Tank Radius in.	x 3.14	= Tank Volume (cubic	: inches)		
Tank Radius				<u></u>	ns/inch	
Tank Volume (cu. in.)	/ 231.01 = Liquid	Capacity —	Gallons / Ta	ank Depth m, = Gallo		
Sludge Level	in. X Gallons Per Inch	= Sludge Vo	olume Gallon	s		
Scum Level	in. X Gallons Per Inch	= Scum Vol	ume Gallon:	5		
Sludge Volume	- + Scum Volume :	≕ Total Sluc	lge and Scum Volume	Gallons		
					%	
Total Sludge and Scu	ım Volume / Liquid (Capacity	= Percent SI	udge and Scum in Tank —		
		≒		*Tanks must be pumped i		
				following conditions exist 1. The top of the sludge la	:: over is less than	
Scum Layer	-1			12 inches from the bottor	n of the outlet	
Effluent			k Depth measured	baffle; or 2. Total sludge and scum	volume is great	
		- P.L	n invert of outlet e to bottom of tank	than 25 percent of the tar	nk's liquid	
Sludge Layer		, p.p.		capacity.		
					-	
		Data	9/11/15	Reset	Form	
Signature	u	Date	1/1///			