

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE DEDORT

JJIJ MAINTENANCE REPORT	
System Location Address (3/ C ()) () + (1) +	
Address 1065/ tentield Aut. Cincle 10 Telephone Number	
City Sti/Water StateMN ZIP 53082 Property ID No./GEO Code	
Owner/VII KE ENSIO Pumping Date	
Contractor AASTIATO	
Maintainer MEYER SEWER MPCA Lie	cense No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1200 Pumped Tank 2: Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 1200
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
	·
-	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X T	Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capa	Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch = Slu	adge Volume Gallons
Scum Level in. X Gallons Per Inch = Scu	um Volume Gallons
Sludge Volume + Scum Volume = Tot	tal Sludge and Scum Volume Gallons
-	- Auto-rate A FEA And And And And And And And And And An
Total Sludge and Scum Volume / Liquid Capac	city = Percent Sludge and Scum in Tank
	*Tanks must be pumped if either of the following conditions exist:
	1. The top of the sludge layer is less than
Scum Layer II	12 inches from the bottom of the outlet baffle; or
Effluent	from invert of outlet 2. Total sludge and scum volume is greate
Sludge Layer	pipe to bottom of tank than 25 percent of the tank's liquid capacity.
AAAA	
Signature (U)	Date 9/11/15 Reset Form