Property address: 7680 Lamar Ave. S.					Inspector initials/Date: ss   12/2/2020				
								(mm/dd/yyyy)	
4. Soil Separation	- Compliance co	ompone	nt #4 of 5						
Date of installation:	7/1/1997 (mm/dd/yyyy)	Unkr		Verific	cation me	ethod(s):	•		
Shoreland/Wellhead protection/Food beverage lodging?		☐ Yes ⊠ No		observ unless	Soil observation does not expire. Previous soil observations by two independent parties are sufficient, unless site conditions have been altered or local				
Compliance criteria:  For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment:		I		requirements differ.					
		☐ Yes	∐ No	7 <u>-1-</u> 3	<ul> <li>         ☐ Conducted soil observation(s) (Attach boring logs)     </li> <li>         ☐ Two previous verifications (Attach boring logs)     </li> </ul>				
				☐ Not applicable (Holding tank(s), no				2 00.600 (00.000)	
				Unable to verify (See Comments/Explanation)					
Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.					0 ■ 100 0000000000000000000000000000000				
				Other (See Comments/Explanation)					
Non-performance systems built April 1, 1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment:		⊠ Yes	□No	Comments/Explanation:					
Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*									
"Experimental", "Other", or "Performance" systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required)		☐ Yes	☐ No	Indicate depths or elevations					
				A. Bottom of distribution media				2'	
				B. Peri	B. Periodically saturated soil/bedrock			6'	
Drainfield meets the designed vertical separation distance from periodically saturated soil or bedrock.				C. Sys	C. System separation			4'	
								3'	
Any "no" answer a	he evetem is			D. Required compliance separation*  *May be reduced up to 15 percent if					
failing to protect gr		iic sysi	ichi is	Ordin				•	
J P J									
F 0	it and Nitraga	- DAAD#	Complia	naa aaw	nonont t	HE of E	⊠ Not	applicable	
5. Operating Perm				9700000		-(200)			
				SUCU PROCESSION		, A below is r	N/O 10=10<11100<0011		
Is the system required				August 1975	If "yes"	, B below is r	equired		
BMP = Best Man	agement Practice(s)	specified	in the systen	n design					
If the answer to bo	oth questions is "	no", this	section de	oes not r	eed to b	e completed	1.		
Compliance criteri	ia								
a. Operating Permit number:					☐Yes	□No			
Have the Operating Permit requirements been met?					1000				
b. Is the required nitrogen BMP in place and properly functioning				ing?	Yes	☐ No			
Any "no" answe	r indicates None	complia	nce.						
Upgrade Requiremen discontinued within ten i ground water, the syster	months of receipt of this	notice or	within a shorter	period if re	equired by lo	ocal ordinance. I	If the syst	em is failing to protect	

is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats