Property address: 12425 53rd Street North		Inspector initials/Date: ss 7/8/2020	
- 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1		1-	(mm/dd/yyyy)
4. Soil Separation - Compliance of	omponent #4 of 5		
Date of installation: 8/31/1990 (mm/dd/yyyy)	Unknown	Verification method(s):	•
Shoreland/Wellhead protection/Food beverage lodging?	⊠ Yes □ No	Soil observation does not expire. Pro observations by two independent pa unless site conditions have been alto	rties are sufficient,
Compliance criteria:		requirements differ.	
For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment: Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.	⊠ Yes □ No	☐ Conducted soil observation(s) (Attach boring logs)	
		Two previous verifications (Attach boring logs)	
		☐ Not applicable (Holding tank(s), no drainfield)	
		☐ Unable to verify (See Comments/Explanation) ☐ Other (See Comments/Explanation)	
Non-performance systems built April 1, 1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment:	☐ Yes ☐ No	Comments/Explanation:	
Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*			
"Experimental", "Other", or "Performance" systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required)	☐ Yes ☐ No	Indicate depths or elevations	
		A. Bottom of distribution media	24"
		B. Periodically saturated soil/bedrock	66"
Drainfield meets the designed vertical separation distance from periodically saturated soil or bedrock.		C. System separation	42"
			0.411
Any "no" answer above indicates	ho evetom ie	Required compliance separation* *May be reduced up to 15 percent if	24"
Any "no" answer above indicates the system is failing to protect groundwater. *May be reduced up to 15 percent if allowed by Local Ordinance.			
5. Operating Permit and Nitrogen BMP* – Compliance component #5 of 5 💮 🖂 Not applicable			
Is the system operated under an Operating Permit?			
Is the system required to employ a Nitrogen BMP? Yes No If "yes", B below is required			
BMP = Best Management Practice(s) specified in the system design			
If the answer to both questions is "no", this section does not need to be completed.			
Compliance criteria			
a. Operating Permit number:			
Have the Operating Permit requirements been met?		☐ Yes ☐ No	
b. Is the required nitrogen BMP in place and properly functioning?		g2	
b. Is the required nitrogen BMP in place and properly functioning?			
Any no answer malcales noncompliance.			
Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.			

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31b • 6/4/14 Page 3 of 3