Property address: 8319 Manning Ave		Inspector initials/Date: ss 1/3/2021
		(mm/dd/yyyy)
4. Soil Separation - Compliance component #4 of 5		
Date of installation: 6/1/1972	Unknown	Verification method(s):
(mm/dd/yyyy) Shoreland/Wellhead protection/Food beverage lodging? Compliance criteria:	☐ Yes ⊠ No	Soil observation does not expire. Previous soil observations by two independent parties are sufficient, unless site conditions have been altered or local
For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment: Drainfield has at least a two-foot vertical	☐ Yes ⊠ No	requirements differ.
		Conducted soil observation(s) (Attach boring logs)
		Two previous verifications (Attach boring logs)
		☐ Not applicable (Holding tank(s), no drainfield) ☐ Unable to verify (see See See See See See See See See See
separation distance from periodically		☐ Unable to verify (See Comments/Explanation)
saturated soil or bedrock.		☐ Other (See Comments/Explanation)
Non-performance systems built April 1, 1996, or later or for non-performance	☐ Yes ☐ No	Comments/Explanation:
systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment:		System needs to be brought up to code. Soils will need to be done in the spring and new design/system.
Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*		
"Experimental", "Other", or "Performance" systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required) Drainfield meets the designed vertical separation distance from periodically saturated soil or bedrock.	☐ Yes ☐ No	Indicate depths or elevations
		A. Bottom of distribution media
		B. Periodically saturated soil/bedrock
		C. System separation
		D. Required compliance separation*
Any "no" answer above indicates to failing to protect groundwater.	he system is	*May be reduced up to 15 percent if allowed by Local Ordinance.
running to protect groundwater.		
5. Operating Permit and Nitrogen BMP* – Compliance component #5 of 5		
Is the system operated under an Operating Permit?		
Is the system required to employ a Nitrogen BMP?		
BMP = Best Management Practice(s) specified in the system design		
If the answer to both questions is "no", this section does not need to be completed.		
Compliance criteria		
a. Operating Permit number:		
Have the Operating Permit requirements been met?		☐ Yes ☐ No
b. Is the required nitrogen BMP in place and properly functioning?		g? Yes No
Any "no" answer indicates Noncompliance.		
Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.		

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31b • 6/4/14