| Business Name: _SS Sep | oticSolutions, LLC. | | | Date. | 7/22/2022 |
|--|--|------------|------------------------------------|---|-----------|
| Soil separation | – Compliance cor | mponent | t #5 of | 5 | |
| Date of installation | 5/1/1992 (mm/dd/yyyy) | Unknov | vn | | |
| Shoreland/Wellhead protection/Food ☐ Yes ☒ No beverage lodging? | | ⊠ No | Attached supporting documentation: | | |
| | | | | ⊠ Soil observation logs completed for the report | |
| Compliance criteria (select one): | | | | ☐ Two previous verifications of required vertical separation | |
| 5a. For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment: | | ⊠ Yes □ No | No | ☐ Not applicable (No soil treatment a | rea) |
| | | | | | - 1. |
| Drainfield has at lea separation distance saturated soil or be | | | | | |
| 5b. Non-performance systems built April 1, 1996, or later or for non- performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment: Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.* | | ☐ Yes ☐ No |] No | Indicate depths or elevations | |
| | | | | A. Bottom of distribution media | 2 |
| | | | | B. Periodically saturated soil/bedrock | 5 |
| | | | | C. System separation | 3 |
| | | | | D. Required compliance separation* | 2 |
| | | | | *May be reduced up to 15 percent if allowed by Local Ordinance. | |
| 2,500 gallons per da | r pre-2008 Rules; ns built under 2008 nr 7080.2400 ctor License required ≤ ay; Advanced Inspector 2,500 gallons per day) e designed vertical from periodically | □ Yes □ |] No | | |

Describe verification methods and results:

Upgrade requirements: (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.