1 of 10

Midwest Sewer Services

651-492-7550/Brian@Midwes	P.O. Box 10853 White Bear Lake, MN 55110 Brian Humpal 651-492-7550/Brian@Midwestsoiltesting.com MPCA Licensed Advanced Inspector						
SUBSURFACE SEWAGE TR	REATMENT SYSTE	M (SSTS) COMPLIANCE REPORT					
Date: 8/31/2022 & 9/1/2022	Time: 12:15 PM	Owner: Geri Wagner					
Inspection Address: 14688 97 th St N, Stillwater Twp, MN 55082							

REPORT SUMMARY

I have performed an "MPCA Compliance Inspection" on this system and have reviewed the original design/permit records on file at Washington County. This very old system (installed in 1990) consists of a pre-cast septic tank and a rock trench drainfield. It should be noted that the average life expectancy of a septic system is approximately 30 years. Pinky's Sewer Service pumped the septic tank on September 1, 2022.

Predicated on my inspection of the system and my review of the original design/permit records, it is my opinion that this system <u>presently meets</u> MPCA minimum compliance inspection requirements.

Midwest Sewer Services have been hired to perform a compliance inspection of this SSTS for compliance with local ordinances pursuant to Minn. Stat. § 115.55 (2013). This compliance inspection covers only the criteria required by Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011). A compliance inspection is an indication of the current compliance status of the system and does not guarantee the performance or longevity of this system beyond the date of inspection, as it is impossible to determine the future performance of any system. Midwest Sewer Services disclaim any use of this compliance inspection beyond determining SSTS compliance pursuant to Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011).

Please contact me should you have any questions.

Christopher Uebe

Brian Humpal

Brian Humpal



Compliance inspection report form

520 Lafayette Road North St. Paul, MN 55155-4194

Existing Subsurface Sewage Treatment System (SSTS)

Doc Type: Compliance and Enforcement

Instructions: Inspector must submit completed form to Local Governmental Unit (LGU) and system owner within 15 days of final determination of compliance or noncompliance. Instructions for filling out this form are located on the Minnesota Pollution Control Agency (MPCA) website at https://www.pca.state.mn.us/sites/default/files/wq-wwists4-31a.pdf.

Property information Local tracking number:					
Parcel ID# or Sec/Twp/Range:	Reason for Inspection	Property Transfer			
Local regulatory authority info: Washington County					
Property address: 14688 ⁹⁷ th St N, Stillwater Twp, MN 55082					
Owner/representative: Geri Wagner		Owner's phone:			
Brief system description: A pre-cast septic tank and a rock trench	drainfield.				

System status

System status on date (mm/dd/yyyy): 9/1/2022

Compliant – Certificate of compliance*

(Valid for 3 years from report date unless evidence of an imminent threat to public health or safety requiring removal and abatement under section 145A.04, subdivision 8 is discovered or a shorter time frame exists in Local Ordinance.)

*Note: Compliance indicates conformance with Minn. R. 7080.1500 as of system status date above and does not guarantee future performance.

Noncompliant – Notice of noncompliance

Systems failing to protect ground water must be upgraded, replaced, or use discontinued within the time required by local ordinance.

An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance or under section 145A.04 subdivision 8.

Reason(s) for noncompliance (check all applicable)

Impact on public health (Compliance component #1) – Imminent threat to public health and safety

Tank integrity (Compliance component #2) – Failing to protect groundwater

Other Compliance Conditions (Compliance component #3) – Imminent threat to public health and safety

Other Compliance Conditions (Compliance component #3) – Failing to protect groundwater

System not abandoned according to Minn. R. 7080.2500 (Compliance component #3) - Failing to protect groundwater

Soil separation (Compliance component #5) – *Failing to protect groundwater*

Operating permit/monitoring plan requirements (Compliance component #4) – *Noncompliant - local ordinance applies* **Comments or recommendations**

Comments of recommendation

Certification

I hereby certify that all the necessary information has been gathered to determine the compliance status of this system. No determination of future system performance has been nor can be made due to unknown conditions during system construction, possible abuse of the system, inadequate maintenance, or future water usage.

By typing my name below, I certify the above statements to be true and correct, to the best of my knowledge, and that this information can be used for the purpose of processing this form.

Business name: Midwest Sewer Services

Certification number: 5342/9852

Inspector signature: Brian Humpal Atta Va

License number: L2896

Phone: 651-492-7550

(This document has been electronically signed)

Necessary or locally required supporting documentation (must be attached)

Soil observation logs System/As-Built Locally required forms Tank Integrity Assessment Operating Permit Other information (list): Report Summary, Property Information, Disclaimer

651-296-6300

Date: 9/1/2022

1. Impact on public health – Compliance component #1 of 5

Compliance criteria:		_ Attached supporting documentation:
System discharges sewage to the ground surface	🗌 Yes* 🛛 No	Other:
System discharges sewage to drain tile or surface waters.	🗌 Yes* 🛛 No	_
System causes sewage backup into dwelling or establishment.	🗌 Yes* 🛛 No	
Any "yes" answer above indicates the system is an imminent threat to public health and safety.		_
Describe verification methods and	results:	

None of the above found.

2. Tank integrity – Compliance component #2 of 5

Compliance criteria:		Attached supporting docu	mentation:		
System consists of a seepage pit,		Empty tank(s) viewed by ins	pector		
cesspool, drywell, leaching pit, or other pit?		Name of maintenance busin	Pinky's Sewer ess: <u>Service</u>		
Sewage tank(s) leak below their		License number of maintenance business: L1673			
designed operating depth?		Date of maintenance:	9/1/2022		
		Existing tank integrity assessment (Attach)			
If yes, which sewage tank(s) leaks:		Date of maintenance (mm/dd/yyyy): (m	nust be within three years)		
Any "yes" answer above indicates the system is failing to protect groundwater.		(See form instructions to en Minn. R. 7082.0700 subp. 4	sure assessment complies with B (1))		
		Tank is Noncompliant (pumping not necessary – explain bel			
		Other:			

Describe verification methods and results:

٠

4	of	1	0
---	----	---	---

Property Address:	14688 97th St N, Stillwater Twp, MN 55082
Business Name:	Midwest Sewer Services

Date: 9/1/2022

3. Other compliance conditions – Compliance component #3 of 5

	За.	Maintenance hole covers appear to be structurally unsound (damaged, cracked, etc.), or unsecured?					
		Yes* No Unknown					
	3b.	Other issues (electrical hazards, etc.) to immediately and adversely impact public health or safety? 🗌 Yes* 🛛 No 🗌 Unknown					
		*Yes to 3a or 3b - System is an imminent threat to public health and safety.					
	3c.	System is non-protective of ground water for other conditions as determined by inspector? \Box Yes* \boxtimes No					
	3d.	System not abandoned in accordance with Minn. R. 7080.2500?					
		*Yes to 3c or 3d - System is failing to protect groundwater.					
	Describe verification methods and results:						
		Attached supporting documentation: 🛛 Not applicable					
4.	Ор	erating permit and nitrogen BMP* – Compliance component #4 of 5 🛛 Not applicable					
	Is th	ne system operated under an Operating Permit?					
	Is th	ne system required to employ a Nitrogen BMP specified in the system design? Yes No If "yes", B below is required					

BMP = Best Management Practice(s) specified in the system design

If the answer to both questions is "no", this section does not need to be completed.

Compliance criteria:

a. Have the operating permit requirements been met?	Yes	No
---	-----	----

b. Is the required nitrogen BMP in place and properly functioning?

Any "no" answer indicates noncompliance.

Describe verification methods and results:

Attached supporting documentation: Operating permit (Attach)

5. Soil separation – Compliance component #5 of 5

Date of installation 1990 (mm/dd/yyyy)	Unknown		
Shoreland/Wellhead protection/Food beverage lodging?	🗌 Yes 🔀 No	Attached supporting documentation:	·
Compliance criteria (select one): 5a. For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment: Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.	Yes No*	 Not applicable (No soil treatment area Reviewed design and permit records.)
 5b. Non-performance systems built April 1, 1996, or later or for non- performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment: Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.* 	Yes No*	Indicate depths or elevations A. Bottom of distribution media B. Periodically saturated soil/bedrock C. System separation D. Required compliance separation* *May be reduced up to 15 percent if allow Ordinance.	See Attached Boring Log(s)
 5c. "Experimental", "Other", or "Performance" systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules 7080. 2350 or 7080.2400 (Intermediate Inspector License required ≤ 2,500 gallons per day; Advanced Inspector License required > 2,500 gallons per day) Drainfield meets the designed vertical separation distance from periodically saturated soil or bedrock. 	Yes No*		

*Any "no" answer above indicates the system is failing to protect groundwater.

Describe verification methods and results:

Upgrade requirements: (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.

<u>Midwest Sower Testing</u> Subsurface Sewage Treatment System Owner/Property Information

This information will be used for the purpose of conducting an MPCA Compliance Inspection.						
Date of Inspection: 8/31/2022 & 9/1/2022	11me: 12:15 PM					
Property Address: 14688 97 th St N, Stillwater Twp, MN Zip: 55082						
Property Owner: Geri Wagner	Phone:					
Tank(s) Tank(s)Material Soil Treatment System Other						
Septic 1 Fiberglass Rock						
	lless trench Experimental system					
	ber trench Cesspool system ge bed Other system					
Other: Block Moun						
Other At-grade	·					
Are the tank maintenance covers accessible? \boxtimes Yes	∇ No *If no proper maintenance must be					
performed through the maintenance holes. Maintena						
the ground surface to facilitate access and proper ma						
the ground surface to racintate access and proper ma	intendice of the system.					
Year house built: 1990 Year septic installed:						
	Number of residents in home?					
	drained by gravity?					
Garbage disposal?	hirlpool bath?					
More than one system (laundry, etc.)?						
Does this property have any footing drain tiles connected to the septic system?						
Are any buildings on this property such as garages or out-buildings connected to this system?						
Are there any additional systems on this property serving other buildings?						
Location of septic system on lot? East Side						
Location of water well on lot? North Side Is the well a deep well? Y						
Have you ever experienced any problems with the system such as: tree roots, sewage back-ups,						
surfacing of sewage onto the ground, septic tank overflowing, etc.; or have any repairs been made						
to the system? If yes, explain:						
5 5 7 1						
When was the system last pumped? 9/1/2022	Name of pumper: Pinky's Sewer Service					
How often pumped in previous years?	Is system on a monitoring plan?					
Have you received notices from any government age						
Is your property located in a shoreland management						
Do you have any additional information that should be given to the new owner?						

 \bigcirc Well House -Septic Tank ○Cleanout Driveway **Drainfield Area** O ST-1 Ν 14688 97th St N Stillwater Twp, MN 55082 NO SCALE

8 of 10

Soil Observations Log

Observations Made By: Midwest Sewer Services Date: 8/31/2022 Classification System: USDA Soil Observation: ST-1 Soil Observation: Surface Elevation of Observation Same ground surface as last drainfield trench Surface Elevation of Observation Surface Elevation of Observation Depth In Inches Rock % Soils Encountered In Inches Soils Encountered 0-8 10YR 2/2 Loamy Fine Sand Rock % Soils Encountered In Inches 10YR 3/4 Silt Loam (Dry) 37-58 ≈15 10YR 4/4 Loamy Sand With Gravel Refusal At 58" 8 Refusal At 58" Refusal At 58" Depth To End Of Soil Observation Or Redox Depth To End Of Soil Observation Or Redox 58" Depth To End Of Soil Observation Relative To System Elevation of Observation Relative To System	Location of Project: 14688 97th St N, Stillwater Twp, MN 55082						
Soil Observation: ST-1 Soil Observation: Surface Elevation of Observation Same ground surface as last drainfield trench Surface Elevation of Observation Depth In Inches Rock % Soils Encountered Inches 0-8 10YR 2/2 Loamy Fine Sand 10YR 3/3 Loamy Fine Sand 10YR 3/4 Silt Loam (Dry) Rock % Soils Encountered 18-37 37-58 ≈15 10YR 4/4 Loamy Sand With Gravel Refusal At 58" Refusal At 58"	Observations Made By: Midwest Sewer Se			ervices		Date:	8/31/2022
Surface Elevation of Observation Same ground surface as last drainfield trench Surface Elevation of Observation Depth In Inches Rock % Soils Encountered In Inches Soils Encountered 0-8 10YR 2/2 Loamy Fine Sand 10YR 3/3 Loamy Fine Sand 10YR 3/4 Silt Loam (Dry) Inches Soils Encountered 18-37 ≈15 10YR 4/4 Loamy Sand With Gravel Refusal At 58" Soils Encountered 8 Refusal At 58" Refusal At 58" Depth To End Of Soil Observation Or Redox Depth To End Of Soil Observation Or Redox	Classifica	tion System:	USDA				
Elevation of Observation Same ground surface as last drainfield trench Elevation of Observation Depth In Inches Rock % Soils Encountered In Inches Rock % Soils Encountered 0-8 10YR 3/3 Loamy Fine Sand 8-18 10YR 3/4 Silt Loam (Dry) In InChes Rock % Soils Encountered 18-37 10YR 3/4 Silt Loam (Dry) 10YR 4/4 Loamy Sand With Gravel In Refusal At 58" 8 × 15 IOYR 4/4 Loamy Sand With Gravel Refusal At 58" In In 8 × 15 IOYR 4/4 Loamy Sand With Gravel In In In 8 × 15 IOYR 4/4 Loamy Component (Interpret) In In In 8 × 15 IOYR 4/4 Loamy Component (Interpret) In In In 8 × 15 IOYR 4/4 Loamy Component (Interpret) Interpret Interpret Interpret 8 × 15 IOYR 4/4 Loamy Component (Interpret) Interpret Interpret Interpret 9 × 10 Interpret Interpret Interpret Interpret Interpret 8 × 15 Interpret Interpret Interpret Interpret Interpret 9 × 10 Interpret </td <td>Soil</td> <td>Observation:</td> <td>ST-1</td> <td></td> <td>Soil Ot</td> <td>oservation:</td> <td></td>	Soil	Observation:	ST-1		Soil Ot	oservation:	
In Rock % Soils Encountered In In Rock % Soils Encountered 0-8 10YR 2/2 Loamy Fine Sand 10YR 3/3 Loamy Fine Sand 10YR 3/4 Silt Loam (Dry) 37-58 10YR 3/4 Silt Loam (Dry) 37-58 ≈15 10YR 4/4 Loamy Sand With Gravel Refusal At 58" Inches Inches 8 8 10YR 3/3 Loamy Fine Sand Inches Inches Inches 37-58 ≈15 10YR 4/4 Loamy Sand With Gravel Inches Inches Inches 8 Refusal At 58" Inches Inches Inches Inches Inches 8 Inches Inches Inches Inches Inches Inches 8 10YR 4/4 Loamy Sand With Gravel Inches Inches Inches Inches 8 Inches Inches Inches Inches Inches Inches 8 Inches Inches Inches Inches Inches Inches 8 Inches Inches Inches Inches Inches Inches Inches 9 Inches Inches <td< td=""><td>Elevation of Observation</td><td>-</td><td></td><td>Elevat Obser</td><td>ion of</td><td></td><td></td></td<>	Elevation of Observation	-		Elevat Obser	ion of		
0-8 10YR 2/2 Loamy Fine Sand 8-18 10YR 3/3 Loamy Fine Sand 18-37 10YR 3/4 Silt Loam (Dry) 37-58 ≈15 10YR 4/4 Loamy Sand With Gravel Refusal At 58" 8 10 <	In Rock %	<u>Soils E</u>	ncountered	In	Rock %	<u>Soils</u>	Encountered
	0-8 8-18 18-37	10YR 3/3 L 10YR 3/4 10YR 4/4 Loar	oamy Fine Sand Silt Loam (Dry) ny Sand With Gravel				
Same Elevation Of Observation Relative To System Elevation Of Observation Relative To System	58" Depth To End Of Soil Observation Or Redox				Depth T	o End Of Soil	Observation Or Redox
-30" Depth To Bottom Of Distribution Media Depth To Bottom Of Distribution Media							Distribution Media
≥28" Of Separation Of Separation	≥28" Of Sep	aration			Of Sep	aration	
End Of Soil Observation At: 58" nd Of Soil Observation At:	End Of Soil O	hservation At-	58"	nd Of 9	Soil Obs	ervation At·	
Limiting Soil Conditions At: None imiting Soil Conditions At:							
Standing Water Present At: None tanding Water Present At:				-			

ottom Of Distribution Medium At: 30 Inches

Signature:

then the

OF COUNTY BUILDING OFFICIAL

Lot 3 Block 1 "ST. CROIX HIGHLANDS"


-SOIL BORINGS-

Soil borings are made in order to determine the type and structure of soils at various depths as well as the location of the water table, Impervious strate or bedrock.

Borings are most easily made with a hand auger, however other expedients may be utilized - back hoe, post hole auger, etc.

Soils encountered at various depths should be listed as to appearance, texture and composition.

Depth at which water, bedrock or heavy clay layer is encountered should be recorded.



Auger Borings: 6/89

LOG OF SOIL BORINGS

BOR	ING NO. 1	BOR	NG NQ 2	BORI	NG NQ 3	BORI	NG NO. 4
DEPTH IN FEET	SOIL DESCRIPTION	DEPTH IN FEET	SOIL DESCRIPTION	DEPTH IN FEET	SOIL DESCRIPTION	DEPTH IN FEET	SOIL DESCRIPTION
0	Gravish Brown Silt Loam	0	very Dark Grayish Brown	0	Very Dark	0	_Silt Loam
1/2		1/2	_Silt_Loam Dark Brown	1/2	Crayish Brown	1/2	Dark
	Brown	I	Silt Loam	1	Brown Silt Loam	I	Brown ·
11/2	Gravelly	11/2	Brown Sandy Loam	11/2		11/2	Silt Loam
2	Oldvollj	2		2	Brown	2	Dark
21/2		21/2	Brown	21/2	to	21/2	Brown
3	Loamy Sand-	3	Loamy	3	Reddish Brown	3	to Reddish
31/2	Sandy	31/2	Sand-	31/2	Sandy Loam	31/2	Brown
4	Loam	4	Sandy Loam	4	Till	4	Sandy Loam
41/2	(End)	41/2	(End)	41/2	(End)	41/2	(End)
5		5		5		5	
51/2	}	51/2		51/2		51/2	
6	}	6		6		6	
61/2		61/2		61/2		61/2	
7	1	7	•	7		7	
71/2		71/2		71/2		71/2	1
8	· ·	8		8		8	T
81/2		81/2		81/2	Ī	81/2	
9		.9		.9		9	

DISCLAIMER

Brian L. Humpal, Inc. dba. Midwest Sewer Services, Inspect Minnesota, Midwest Soil Testing Relative to Subsurface Sewage Treatment System (SSTS) Compliance Inspections

- 1. This inspection/report is being performed for only the seller/owner of the property on which the SSTS is located. In such case that another party is paying for the inspection, the contract is between only said party and Brian L. Humpal, Inc.; there is no contract between Brian L. Humpal, Inc. and any other party unless otherwise noted.
- 3. Brian L. Humpal, Inc. has not been retained to warranty, guarantee, or certify the proper functioning of the SSTS for any period of time beyond the date of inspection or into the future. Because of the numerous factors (usage, maintenance, soil characteristics, previous failures, etc.) which may affect the proper operation of an SSTS, as well as the inability of Brian L. Humpal, Inc. to supervise or monitor the use or maintenance of the SSTS, the report shall not be construed as a warranty by Brian L. Humpal, Inc. that the SSTS will function properly for any particular party for any period of time.
- 4. Brian L. Humpal, Inc. is unable to verify the frequency and/or, quality of prior or future maintenance of the SSTS. Maintenance of the tank(s) must be performed through the tanks maintenance hole. The removal of solids from any location other than the maintenance hole is not a compliant method of maintenance. It is strongly recommended that maintenance covers be made accessible to the ground surface to facilitate proper maintenance.
- 5. Minimum Compliance Inspection requirements relative to this inspection and this report include <u>only</u> verification that the SSTS has tank(s) (septic tanks, lift tanks, dosing tanks, stilling tanks, etc.) which are watertight below the designed operating depth, the required separation between the bottom of the subsurface soil distribution medium and seasonally saturated soils, no back-ups of sewage into the dwelling, no discharge of sewage/effluent to the ground surface or surface waters, and no imminent safety hazards. Brian L. Humpal, Inc. does not inspect plumbing or pumps prior to the first SSTS component as these are plumbing components. The performance of exterior pumps and associated components are not inspected as they are considered to be maintenance items. Additionally, no indications relative to compliance with electrical code requirements have been made. It is recommended that any other applicable plumbing, electrical, housing, etc. inspections be performed by a qualified inspection business. Sewage back-up verification is limited to observing the floor drain area and/or the information supplied by the last occupants of the building prior to inspection. Brian L. Humpal, Inc. cannot guarantee that the information given to them by the last occupants of the building prior to inspection relative to back-ups is accurate.
- 4. Certification of this SSTS does not warranty future use beyond the date of the inspection. Any SSTS, old or new, can become hydraulically overloaded or discharge sewage/effluent to the ground surface as a result of more people moving into the house than were previously occupying the house, improper maintenance, heavy usage, leaking plumbing fixtures, groundwater infiltration, tree roots, freezing conditions, surface drainage problems, poor initial design, poor construction practices, or unsuitable materials used in constructing the system; the system can also simply stop working because of its age. An SSTS that has been properly designed and installed, properly maintained, and used in the manner for which the system was designed can be expected to provide service for twenty to twenty-five years on average. Some parts of the SSTS such as alarms, switches, pumps, filters, etc. will most likely have to be repaired or replaced over the lifetime of the system.
- 5. A Compliance Inspection is not meant to be a test or inspection for longevity of the system; a Compliance Inspection is strictly for the purpose of determining if the SSTS is protective of public health and safety, as well as the groundwater at the date and time the inspection was performed. This inspection is not intended to determine if the SSTS was originally designed or installed to past or present MPCA or other Local Government Unit code requirements. This inspection is not intended to determine if the SSTS was designed and/or installed to support the anticipated flow from the building as the use of the building may have changed since the design and construction of the SSTS due to the addition of bedrooms, occupants, etc. In addition, this inspection is not intended to determine the quality of the original SSTS design, the quality of the construction practices used while installing the SSTS, or the quality of the materials used in constructing the SSTS.
- 6. Brian L. Humpal, Inc. cannot guarantee the performance of SSTS products/components such as: gravelless pipe, chamber trenches, effluent filters, tanks, sewage pre-treatment components, piping, etc. Products such as gravelless pipe are no longer approved for installation in the State of Minnesota and may have a significantly reduced performance and/or life expectancy.
- 7. WINTER WORK: By accepting this report, it is understood that inspections conducted during winter months (approximately November 1st through April 1st) are more difficult to perform because of possible snow cover and/or ground frost. SSTS components such as tanks, maintenance covers, tank inspection pipes, subsurface distribution medium inspection pipes, and soil treatment areas are more difficult or impossible to locate due to snow cover and/or ground frost. In addition, soil borings are more difficult to perform due to snow cover and/or ground frost. Brian L. Humpal, Inc. will attempt to use the same level of standards when performing work during winter periods as when performing work during non-winter periods. However, the recipient of this report understands that because of the aforementioned considerations, the same level of standards may not be possible.
- 8. By accepting this report, the client understands that Brian L. Humpal, Inc. will not be responsible for any monetary damages exceeding the fee for the services provided.