2002 Soils

(Subject to Review and Approval of Officials)

Lot 4, Flock 1
"BMFRALD HIGHLANDS"
Pt. of St Sec. 22,
T29N K20N (West Lakeland)


-SOIL BORINGS-

Soil borings are made in order to determine the type and structure of soils at various depths as well as the location of the water table, impervious strata or bedrock.

Borings are most easily made with a hand auger, however other expedients may be utilized - back hoe, post hole auger, etc.

Soils encountered at various depths should be listed as to appearance, texture and composition.

Depth at which water, bedrock or heavy clay layer is encountered should be recorded.



Date: October 2001

Soil Borings: RS Johnson Soil Testing

LOG OF SOIL BORINGS

BORING NO. 1A		BORING NO. 2A		BORING NO.		BORING NO.	
DEPTH IN FEET	SOIL DESCRIPTION	DEPTH IN FEET	SOIL DESCRIPTION	OEPTH IN FEET	SOIL DESCRIPTION	OEPTH IN FEET	SOIL DESCRIPTION
0	Very Dark Brown	0	Very Dark Brown Silt Loam	0		0	
1/2	Silt Loam	1/2	Dark Brown	1/2		1/2	
1	Brown	1	Silt Loam Yellowish Brown	I		1	÷
11/2	Silt Loam	11/2	Silt Loam	11/2		11/2	
2	Dark Brown (7.5YR 4/4)	2	Dark Brown	2		2	•
21/2	Sandy Loam	21/2	(7.5YR 4/4)	21/2		21/2	
3	Dark Brown	3		3		3	
.31/2	Sandy Loam (dense)	31/2		31/2		31/2	;
4	Dark Brown	4	Sandy Loam	4		4	
41/2	(7.5XR 4/4)	41/2		41/2		41/2	
5	Gravelly	5	Yellowish Brown	5		5	
51/2	Loamy Sand	51/2	Gravelly Sandy Loam	51/2		51/2	
6	(End)	6	(End)	6		6	
61/2		61/2		61/2		61/2	
7		7		7		7	
71/2	Mottling	71/2	Mottling	71/2		71/2	
8	Depth:	8	Depth:	8		8	
81/2		81/2		81/2		81/2	
9		9		9		9	2