

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 13020-9445 S+N	Telephone Number 651-439-5
City Still Water State MN ZIP 55056 Property ID No./GEO Code	
Owner John Harrington Pumping Date 9-1-16	
Contractor	
Maintainer R&M Septic MPCA License No. 7708 L 3070 Telephone Number (651) 674-8520	
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: / 500 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Z Yes No (If no provide measurements below)	Total Gallons Pumped: / (A)
	NOTE: This does not some an according to the source of the
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
·	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. \mathbf{X} Tank Width in, \mathbf{X} Tank Depth in. $\mathbf{=}$ Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Slud	lge Volume Gallons
	n Volume Gallons
Sludge Volume	al Sludge and Scum Volume Gallons
Total Sludge and Scum Volume/ Liquid Capacity = Percent Sludge and Scum in Tank %	
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature Reset Form Date 9-1-16 Reset Form	