

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location
Address 16614 Fenway Ave N Telephone Number 612-516-12=
City Hugo State MN ZIP 5503 Property ID No./GEO Code
Owner Pat Ash Pumping Date 9-28-16
Contractor
Maintainer R&M Septic MPCA License No. 7708 L 3070 Telephone Number (651) 674-8520
What was done to the system? Report Liquid Capacity in Gallons
Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Total Gallons Pumped: 2500 Pumped Tank 2: 1500 Pumped Tank 4: Pumped Total Gallons Pumped: 2500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.
9000
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons
Scum Level in. X Gallons Per Inch = Scum Volume Gallons
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Tank Depth measured from invert of outlet pipe to bottom of tank *Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.