

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 20310 ()004 Av	Telephone Number (5) -592-6262
	te MN ZIP 55056 Property ID No./GEO Code
Owner Steve Booth Pumping Date 10-6-16	
Contractor	
Maintainer R&M Septic MPCA License No. 2708 3070 Telephone Number (651) 674-8520	
What was done to the system?	Report Liquid Capacity in Gallons
☐ Tank(s) Pumped ☐ Sludge and scum measured. Do tanks need to be pumped? ☐ Yes ☐ No (If no provide measurements below)	Tank 1: 1250 Pumped Tank 2: Pumped Tank 3: Pumped Tank 4: Pumped Total Gallons Pumped: 1250
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature Richard Clynthy	Date / ()- / Reset Form