

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

	System Location	
Address 5540 Henna C	t. N. T	elephone Number
city fine Springs	State ZIP 5572 SProper	rty ID No./GEO Code
Owner Mark Anderson	Pumping Date 0 10 16	
	Contractor	The second secon
Maintainer Boss Pumping	MPCA License No. 1945 To	elephone Number (651) 466-0800
What was done to the system?		Liquid Capacity in Gallons
Tank(s) Pumped	1411K 1.1200	Pumped Tank 2: Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3:	Pumped Tank 4: Pumped
Yes No (If no provide measurements b	elow) Total Gallons Pumped	d:
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.		
*Tank:Measurements-Use Only:If Tank(s):Were NOT Pumped		
		ank Volume (cubic inches)
Tank Length in. X Tank Width		
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in, = Gallons / Inch		
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons		
Scum Level in. X Gallons Per Inch = Scum Volume Gallons		
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %		
Scum Layer Effluent Sludge Layer	Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
	(A) (A)	