

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

	System Location (1986)
Address 9798 - 55th St. N	. Telephone Number
city Lake Elmo	State ZIP 55042 Property ID No./GEO Code
Owner Steve Sandberg	Pumping Date 10/12/16
	Contractor.
Maintainer Boss Pumping	MPCA License No. 1945 Telephone Number (651) 466-0800
What was done to the system?  Tank(s) Pumped  Sludge and scum measured.  Do tanks need to be pumped?  Yes No (If no provide measurements be Visual Inspection (note any problems with the	
*Tank Measure	ments-Use Only if Tank(s) Were NOT Pumped
Tank Length in. <b>X</b> Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. <b>X</b> Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Li	iquid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. <b>X</b> Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Lic	quid Capacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
at A	Date 10-12-14