

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

Address 5630-180 City Forest Lak	th < 1 A		 -
City France LAK	→ >+ · 10 ·		elephone Number
	State	ZIP 5503 8 rope	rty ID No./GEO Code
Owner Brian Large	Pumping Dat	te 10/20/	16
	Çəni	ractor	
Maintainer Boss Pumping	MPCA License	e No. 1945 1	elephone Number (651) 466-0800
What was done to the syst I ank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measured) Visual Inspection (note any problem)	urements below)	Tank 1: /0(0) Tank 3: Total Gallons Pumpe	Pumped Tank 2: 1000 Pumped Pumped Tank 4: Pumped d: 1000 not serve as a compliance inspection.
Visual Inspection (1.000 day)			
	•		
*Tank Measurements-Use Only (f Tank (s) Were-NOT Pumped			
Tank Length in. X Tank Wid	th in. X Tank	Depth in =	Fank Volume (cubic inches)
Tank Radius in. X Tank Rad	ius in. X 3.1 4	4 = Tank Volume (cubic	c inches)
Tank Volume (cu. in.) / 23	1.01 = Liquid Capacity	Gallons / Ta	ank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Pe	er Inch = Sludge	Volume Gallon	S
Scum Level in. X Gallons Po	er Inch = Scum V	olume Gallon	S
Sludge Volume + Scum Vol	ume = Total SI	ludge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %			
Scum Layer		ank Depth measured	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater
Sludge Layer		ipe to bottom of tank	than 25 percent of the tank's liquid capacity.